

US010324492B2

(12) United States Patent

Pantel

(54) SMARTPHONE WITH FRONT CAMERA AND MAXIMIZED DISPLAY SCREEN

- (71) Applicant: Lothar Pantel, Neckargemuend (DE)
- (72) Inventor: Lothar Pantel, Neckargemuend (DE)
- (73) Assignee: inodyn NewMedia GmbH, Neckargemuend (DE)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
- (21) Appl. No.: 15/856,305
- (22) Filed: Dec. 28, 2017

(65) Prior Publication Data

US 2018/0219987 A1 Aug. 2, 2018

Related U.S. Application Data

(63) Continuation of application No. 29/539,390, filed on Sep. 14, 2015, now Pat. No. Des. 810,713.

(30) Foreign Application Priority Data

Jun. 29, 2017 (GB) 1710466.2

- (51) Int. Cl. *G06F 1/16* (2006.01) *H04M 1/02* (2006.01) (Continued)
- (52) U.S. Cl. CPC *G06F 1/1605* (2013.01); *G02F 1/13338* (2013.01); *G06F 1/1626* (2013.01); (Continued)
- (58) Field of Classification Search CPC H04M 1/0264–0266; G06F 1/1605–1686; G06F 3/041–0416;

(Continued)

(10) Patent No.: US 10,324,492 B2

(45) **Date of Patent:** Jun. 18, 2019

References Cited

(56)

U.S. PATENT DOCUMENTS

D645,833 S 9/2011 Seflic et al. D665,763 S * 8/2012 Tsai D14/138 G (Continued)

FOREIGN PATENT DOCUMENTS

EM	004013787-0001	S	7/2017
EM	004494417-0001	S	11/2017

OTHER PUBLICATIONS

Samsung Galaxy S IV Design Places the Front Camera at the Bottom, Mar. 7, 2013, available at https://www.concept-phones. com/samsung/samsung-galaxy-iv-design-places-front-camera-bottom/ (Year: 2013).*

(Continued)

Primary Examiner — Gennadiy Tsvey

(57) **ABSTRACT**

A smartphone device may have thin borders at the left, right, top, and/or bottom edges of the display screen. To accommodate, e.g., a front camera in spite of a border that is too thin for a camera module and lens, at least one corner of the display may be cut out. Optical sensor(s), emitter(s), or the lens of a front camera may be disposed at the location(s) of the cutout(s). A wide-screen movie may be displayed in letterbox mode with horizontal bars above and/or below the movie, wherein the cutout(s) are located, at least partially, in the region(s) of the horizontal bars, thereby avoiding that larger parts of the movie are hidden by the cutout(s). In other embodiments, an uninterrupted status bar may be displayed between a cutout in the upper-left corner and a cutout in the upper-right corner of the display.

20 Claims, 16 Drawing Sheets



(51) Int. Cl.

(2006.01)
(2006.01)
(2006.01)
(2006.01)

(58) Field of Classification Search CPC ... G02F 1/13338; G02F 3/041; G09G 3/2092;

G09G 2340/04–2354/00; H01L 27/323 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D693,787	S	11/2013	Reivo et al.
D695,250	S *	12/2013	Kim D14/138 G
D717,263	S	11/2014	Wozniak
8,996,082	B2	3/2015	Tam
D730,863	S	6/2015	Yamagishi et al.
D734,326	S	7/2015	McManigal
D747,713	S	1/2016	Choi et al.
D749,551	S	2/2016	Mitchell
D752,040	S	3/2016	Cebe et al.
D762,628	S *	8/2016	Yoon D14/248
9,405,391	B1	8/2016	Mackraz
D767,563	S	9/2016	Satzger et al.
D772,835	S	11/2016	Kim et al.
D776,108	S	1/2017	Hsu
D777,700	S *	1/2017	Kwon H04N 5/2258
			D14/138 G
9,560,254	B2 *	1/2017	Lombardi H04N 5/2258
D780,147	S	2/2017	Song
D780,710	S	3/2017	Song
D783,565	S *	4/2017	Kim D14/138 G
D783,566	S *	4/2017	Kim D14/138 G
D784,281	S *	4/2017	Ryu D14/138 G
D784,314	S *	4/2017	Ryu D14/248
D786,214	S *	5/2017	Kwon D14/138 G
D788,731	S *	6/2017	Park D14/138 C
D794,004	S *	8/2017	Kwon D14/248
D794,623	S *	8/2017	Kwon D14/248
D798,263	S *	9/2017	Kwon D14/138 G
2002/0147033	A1*	10/2002	Ban H04N 7/142
			455/566
2006/0284850	A1	12/2006	Tokkonen

2008/0309637	A1*	12/2008	Lim G06F 1/1624
			345/173
2009/0060452	A1*	3/2009	Chaudhri H04N 5/445
			386/239
2012/0032979	A1	2/2012	Blow et al.
2012/0105400	A1*	5/2012	Mathew H04N 5/2251
			345/207
2013/0321740	A1*	12/2013	An H05K 5/0217
			349/58
2014/0135071	A1	5/2014	Lee et al.
2015/0077629	AI	3/2015	leong
2015/0077625	A1*	3/2015	Gulick Ir G06E 1/1632
2015/0005075	л	5/2015	726/25
2015/0220840	A 1 *	8/2015	20/33 Shin H0/N 1/00207
2013/0229849	AI	0/2015	248/207 1
2015/0251202		0/2015	348/20/.1
2015/02/1392	AI	9/2015	Musgrave et al.
2015/0287164	Al*	10/2015	Kominar G06T 3/0093
			345/647
2015/0347732	A1*	12/2015	Alameh G06F 21/32
			726/19
2016/0132464	A1	5/2016	Imana
2016/0132470	A1	5/2016	Imana
2016/0240173	A1	8/2016	Bostick et al.
2016/0313593	A1	10/2016	Grip
2017/0004798	A1*	1/2017	Park
2017/0123452	A1	5/2017	Evans et al.
2017/0123453	ÂÎ	5/2017	Evans et al.
2017/0123454	A1	5/2017	Evans et al.
2017/0123575	AI	5/2017	Evans et al.
2017/0124933	AI	5/2017	Evans et al.
2017/0126937	AI	5/2017	Evans et al
2017/0126979	AI	5/2017	Evans et al
2017/0162111	AI	6/2017	Kang et al
2017/0168463	A1	6/2017	Hong et al
2018/0121724	A1*	5/2017	Overannikov C06K 0/00617
2010/0121/24	AT,	5/2018	Ovsiaimikov GOOK 9/0001/

OTHER PUBLICATIONS

Early publication of UK patent application—published by the inventor/applicant of the present application. Twelve-Month Grace Period Applies; Inventor/author: Lothar Pantel; Title: "Front-facing camera and maximized display screen of a mobile device;" Publication Date: Jul. 3, 2017; Available online from: http://www.earlypublication.com.

Alex Hern, May 30, 2017, "Android co-founder reveals new smartphone to take on Apple and Samsung," The Guardian, Available online from: https://www.theguardian.com/technology/2017/may/30/essential-phone-android-co-founder-reveals-new-smartphone-apple-samsung.

Samuel Gibbs, Nov. 10, 2017, "iPhone X review: Apple finally knocks it out of the park," The Guardian, Available online from: https://www.theguardian.com/technology/2017/nov/10/iphone-x-review-apple-face-id-all-screen-design-home-button.

* cited by examiner







FIG. 3 (prior art)



FIG. 4 (prior art)









FIG. 11



FIG. 12













FIG. 17







FIG. 19



FIG. 21







FIG. 27

5

SMARTPHONE WITH FRONT CAMERA AND MAXIMIZED DISPLAY SCREEN

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of U.S. application Ser. No. 29/539,390, filed Sep. 14, 2015, now U.S. Pat. No. D810,713 S. The benefit of the above prior application is claimed and the entire disclosure of the prior ¹⁰ application, including the unabridged description, as originally filed on Sep. 14, 2015, is expressly incorporated herein by reference. This application claims priority from United Kingdom Patent Application No. 1710466.2, filed Jun. 29, 2017. ¹⁵

TECHNICAL FIELD

The present invention relates to smartphones and, in particular, to methods and systems that maximize the display ²⁰ screen of a smartphone while providing a high-quality, front-facing camera.

BACKGROUND OF THE INVENTION

Common smartphones, phablets, or comparable mobile electronic devices contain a front-facing camera placed on the front side of the mobile electronic devices. The front side of the mobile electronic devices also contains a display screen, using a display technology such as liquid-crystal 30 display (LCD) or active-matrix organic light-emitting diode (AMOLED).

For example, the display may use an LC panel. The LC panel may include a thin film transistor (TFT) substrate, a color filter substrate, and LC molecules injected between the 35 TFT substrate and the color filter substrate. The TFT substrate may include gate lines and data lines implemented as matrices. Thin film transistors (TFT) may be formed at crossing points of the gate lines and the data lines. A signal voltage is applied to a common electrode disposed between 40 a pixel electrode and the color filter substrate. Liquid crystal molecules are aligned between the pixel electrode and the common electrode according to the signal voltage, thereby controlling light transmittance. The color filter substrate may include a color filter and a common electrode, the color 45 filter having red, green, and blue filters repeatedly formed in a state where black matrices are disposed therebetween. The common electrode may be formed of a transparent conductive material, such as indium tin oxide (ITO) or indium zinc oxide (IZO).

A pair of polarizers may be arranged on the upper and lower surfaces of the LC panel. The polarizers may be arranged to cross each other. The polarizer disposed under the LC panel serves to polarize light incident onto the LC panel, and the polarizer formed on the LC panel serves as an 55 analyzer. A backlight unit may be disposed beneath the LC panel. The backlight unit may include a diffusion sheet, a reflection sheet, and a prism sheet.

In another example, the display panel may be implemented as an AMOLED display consisting of several layers, 60 e.g., cathode layer, organic active layers, thin-film transistor (TFT) array, and substrate. An active matrix of OLED pixels generates light (luminescence) upon electrical activation. The active matrix of OLED pixels may be deposited or integrated onto the thin-film transistor (TFT) array, which 65 functions as a series of switches to control the current flowing to each individual pixel. Known TFT backplane

technologies, such as polycrystalline silicon (poly-Si) and amorphous silicon (a-Si), may be used. The display panel may be a flexible display, which enables the display panel to be bent, rolled, or curved at the edges. For example, a flexible OLED-based display may comprise a flexible substrate on which the electroluminescent organic semiconductor is deposited. Optionally, the display panel may have an in-cell touch panel that integrates a capacitive sensor array.

The display screen may be rectangular with an aspect ratio of, for instance, 16:9, 2:1, 19.5:9, or 21:9. Furthermore, display panels with a round shape are known from the prior art. More information about the assembly and structure of round displays (e.g., for smartwatches) can be found, inter alia, in patent application US2017/0168463 A1, titled "Display panel with minimum borders" and patent application US2016/0313593 A1, titled "Divided backlight configuration of a display."

A smartphone with a rectangular display screen may be oriented horizontally or vertically by the user, which may result in operating modes known as "landscape mode" and "portrait mode," respectively. The page orientation can also be described with the terms "landscape orientation" and "portrait orientation."

A user may hold the smartphone horizontally (landscape 25 mode) and may watch a video or movie displayed in full screen mode on the display screen. A feature film or a wide-screen movie may have an aspect ratio of, e.g., 2.35:1, 2.39:1, 2.40:1, or 2.66:1. If the wide-screen movie has an aspect ratio that is wider, i.e., greater, than the aspect ratio 30 of the display screen, the wide-screen movie frames may be displayed on the display screen in a mode known as "letterbox": horizontal bars, typically black bars, are inserted above and below the wide-screen movie.

The display screen of a smartphone typically does not occupy the full front side of the smartphone because a wide border is required at the top and/or at the bottom of the front side to accommodate the lens of a front-facing camera and also to accommodate other optical or acoustic sensors and emitters. As a result, the size of the display screen is reduced.

The front-facing camera of a smartphone may be used for video telephony or to take a self-portrait photograph, commonly known as a "selfie." In recent years, the resolution of the front-facing camera has increased, and it is likely that the resolution will continue to increase in the future (e.g., from 8 megapixels to 13 megapixels) to enable the user to take "selfies" of the highest quality and to record high-quality 4K videos. Therefore, high-quality camera lenses for the frontfacing camera and an undisturbed light path are essential.

Patent applications US2017/0123454 A1, US2017/ 0123453 A1, and US2017/0123452 A1, titled "Camera integrated into a display," patent application US2017/ 0123575 A1, titled "Optical sensors disposed beneath the display of an electronic device," patent application US2017/ 0124933 A1, titled "Mobile device with display overlaid with at least a light sensor," patent applications US2017/ 0126979 A1 and US2017/0126937 A1, titled "Apparatus and method to maximize the display area of a mobile device," and patent application US2015/0271392 A1, titled "System and method for coordinating image capture in a camera hidden behind a display device," suggest disposing the front-facing camera beneath the display screen of the smartphone. However, depending on the display technology of the screen (e.g., LCD, OLED, Micro-LED, etc.), small opaque or semi-transparent structures that may be necessary for the operation of the display screen may blur or cloud the resulting picture of the front-facing camera, because the light path must pass through the display screen. Further-

10

more, LCD panels often also require removing a diffuser layer to adapt them for use as transparent displays, and the polarizing filters of the LCD panels inherently limit the transmission efficiency of unpolarized light. This may reduce the light sensitivity of a front-facing camera located ⁵ beneath the display screen, especially in low-light conditions.

SUMMARY OF THE INVENTION

Aspects of the present disclosure are directed to mobile electronic devices with a display screen and at least one front-facing camera, optical sensor, and/or emitter, such as smartphones or phablets. In embodiments of the present 15 invention, a smartphone may have very thin borders at the top, bottom, left, and/or right edges of the display screen. To accommodate an optical sensor, such as a front camera, in spite of a border that is too thin for the optical sensor (e.g., camera module and lens), at least one corner of the display $_{20}$ panel may be cut out such that a recess is created. An optical sensor and/or emitter or the lens of a front camera may be disposed at the location of the recess or cutout. Optionally, in some embodiments, the recess or cutout may have a convex shape for the most part, thereby maximizing the 25 remaining screen area.

Depending on the embodiment, a wide-screen movie may be displayed on the display screen in letterbox mode (landscape orientation using the full width of the display screen) such that the (e.g., black) bars above and below the widescreen movie are at least partially located in the region of the cutout(s), thereby reducing or preventing the problem that parts of the movie are invisible (i.e., hidden) due to the cutout(s). For example, a smartphone (with a front camera or a front-facing optical sensor) may be made for maximizing the size of a wide-screen movie in relation to the outer dimensions of said smartphone, and may comprise:

- a) an oblong display, said display being aligned in landscape orientation and having a horizontal screen width, 40 at least an upper corner, and at least a lower corner, wherein said display has an upper cutout at said upper corner and a lower cutout at said lower corner, said upper cutout having an upper cutout area, and said lower cutout having a lower cutout area, 45
- b) a computer system configured to be at least able to alternately display a first screen content and a second screen content on said display,

c) said first screen content comprising:

- i) a wide-screen movie in landscape orientation that 50 seamlessly extends over the entire horizontal screen width of said display, said wide-screen movie having a left side, a right side, and an image width, wherein said wide-screen movie is displayed horizontally between said upper cutout and said lower cutout, 55
- ii) an upper horizontal matte region located above said wide-screen movie, wherein said upper horizontal matte region extends into said upper cutout area, such that said upper cutout is accommodated, at least in part, in said upper horizontal matte region,
- iii) a lower horizontal matte region located below said wide-screen movie, wherein said lower horizontal matte region extends into said lower cutout area, such that said lower cutout is accommodated, at least in part, in said lower horizontal matte region,
- d) at least one front camera module with at least one lens disposed, at least in part, in said upper cutout area or

4

said lower cutout area, and at least one optical emitter disposed, at least in part, in said lower cutout area or said upper cutout area,

- e) an oblong casing with at least a first thin border and a second thin border, said casing being aligned in landscape orientation and having an outer horizontal measurement, wherein said first thin border is disposed adjacent to the left side of said wide-screen movie and said second thin border is disposed adjacent to the right side of said wide-screen movie, such that the outer horizontal measurement of said casing is nearly equal to the image width of said wide-screen movie,
- f) said second screen content comprising:i) an image having a visible area, and
 - ii) a schematized camera lens symbol located adjacent to said upper cutout area or said lower cutout area, wherein said schematized camera lens symbol surrounds said upper cutout area or said lower cutout area substantially in a quarter circle, such that the visible area of said image is maximized, said schematized camera lens symbol being visible, at least if said front camera module is active.

The aforementioned and many further aspects, variants, objectives, and advantages of the invention will be comprehensible to those skilled in the art after reading detailed descriptions of the embodiments.

BRIEF DESCRIPTION OF THE DRAWINGS

Further features, advantages, and potential applications will be apparent from the drawings. All described and/or illustrated features, alone or in any combination, independent of the synopsis in individual claims, constitute the subject matter of the invention.

FIG. 1 shows a conventional smartphone (prior art).

FIG. 2 shows a sectional view of the smartphone of FIG. 1 (prior art).

FIG. **3** shows another sectional view of the smartphone of FIG. **1** (prior art).

FIG. **4** is a diagrammatic representation of the computer system of a smartphone (prior art).

FIG. **5** is a top plan view of an embodiment of the mobile electronic device in accordance with the present invention. The housing of the mobile electronic device is characterized by a very thin border or edging at least at the upper edge, left edge, and right edge of the display screen. The lens of a front camera module, optical sensor, and/or optical emitter is located at least in the upper right-hand corner, as shown in the drawing. Both, the display screen and the lens in the upper right-hand corner are covered by a transparent or semi-transparent material, such as glass. For illustrative purposes, the display screen shows a gray color by means of standard drafting symbol patterns. This color (e.g., dark gray) could represent the display screen in the switched-off state.

FIG. **6** is a top/front perspective view of an embodiment of the mobile electronic device in accordance with the present invention. For illustrative purposes, the display screen shows the self-portrait of a woman that may have 60 been taken by the front camera.

FIG. 7 is a bottom view thereof.

FIG. 8 is a rear view thereof.

FIG. 9 is a front view thereof.

FIG. **10** is a left side view thereof, the right side being a ⁶⁵ mirror image thereof.

FIG. **11** is a top plan view of an embodiment of the mobile electronic device in accordance with the present invention.

A lens is located at least in one corner. The display screen shows a status bar that has approximately the height of the recess surrounding the lens of the front camera module, optical sensor, and/or optical emitter. Furthermore, the display screen shows schematized app icons of a start screen. 5 The bottom view, rear view, front view, and left/right side views of the embodiment correspond to FIG. 7, FIG. 8, FIG. 9, and FIG. 10, respectively.

FIG. 12 is a top plan view of an embodiment of the mobile electronic device in accordance with the present invention. 10 A lens is located at least in one corner. The display screen shows a letterboxed wide-screen movie frame (e.g., black bars above and below the movie). The bottom view, rear view, front view, and left/right side views of the embodiment correspond to FIG. 7, FIG. 8, FIG. 9, and FIG. 10, respec-15 tively.

FIG. 13 is a top plan view of an embodiment of the mobile electronic device in accordance with the present invention. The general description of FIG. 11 applies.

FIG. 14 is a top plan view of an embodiment of the mobile 20 electronic device in accordance with the present invention. The general description of FIG. 12 applies.

FIG. 15 is a top plan view of an embodiment of the mobile electronic device in accordance with the present invention. A lens is located at least in one corner. The display screen 25 shows a status bar at the top, onscreen soft keys for the navigation at the bottom, and the chat dialog of a communication app. The bottom view, rear view, front view, and left/right side views of the embodiment correspond to FIG. 7, FIG. 8, FIG. 9, and FIG. 10, respectively.

FIG. 16 is an enlarged view showing an exemplary shape of the upper right-hand corner.

FIG. 17 is an enlarged view showing another exemplary shape of the upper right-hand corner.

FIG. 18 is an enlarged view showing yet another exem- 35 plary shape of the upper right-hand corner.

FIG. 19 is an enlarged view showing yet another exemplary shape of the upper right-hand corner.

FIG. 20 is an enlarged view showing yet another exemplary shape of the upper right-hand corner.

FIG. 21 is an enlarged view showing yet another exemplary shape of the upper right-hand corner.

FIG. 22 illustrates further details of exemplary embodiments.

FIG. 23 is a top/front perspective view of an embodiment 45 of the mobile electronic device in accordance with the present invention. The lens of a front camera module is located at least in the upper right-hand corner. The display screen shows the self-portrait of a woman that may have been taken by the front camera. Furthermore, the display 50 screen shows a schematized camera lens symbol, which may be animated and which may indicate an active front camera.

FIG. 24 is a bottom view of an embodiment wherein the rear side of the smartphone is characterized by a fully symmetrical arrangement.

FIG. 25 is a rear view thereof.

FIG. 26 is a front view thereof.

FIG. 27 shows a left side view of an embodiment with a slightly curved display screen (instead of a flat display screen, as shown in FIG. 10).

60

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 (labeled "prior art") shows a conventional smart- 65 phone 100 as an example of a mobile electronic device. The drawing illustrates a display screen 101 with touchscreen

6

functionality, the lens 102 of a front-facing camera, an earpiece 103 (ear speaker for telephone calls), and optical sensors and/or emitters 104. An optical sensor 104a may be, for instance, a combined proximity and light sensor and an optical emitter 104b may be, for instance, a flash LED or an infrared (IR) LED to illuminate the face of the user. Alternatively, the optical emitter 104b may be a status LED that indicates operating states, such as "on/off" or "charging battery." A graphics sub-system 106 (integrated into the smartphone 100 and shown in dotted lines in FIG. 1) is responsible for generating the screen content displayed on the display screen 101.

As can be seen in FIG. 1, conventional smartphones 100 typically feature a thin border 105 at the left and right edge of the display screen 101. It can also be seen that in the example of FIG. 1, a wide border is required at least at the top of the front side of the smartphone 100 to accommodate the lens 102 (front camera), the earpiece 103 (for the ear speaker), the optical sensor 104a (e.g., proximity sensor or light sensor), and the optical emitter 104b (e.g., LED indicator or IR-LED).

FIG. 2 and FIG. 3 (both labeled "prior art") show sectional views of the smartphone 100 taken at the sectioning plane and in the direction indicated by section lines 2-2 and section lines 3-3 (in FIG. 1). A smartphone 100, as known from the prior art, may comprise several layers: The front side of the smartphone's casing 100 may consist of a cover glass 202. A rectangular display panel 201 may be disposed beneath the cover glass 202, and a printed circuit board 203 (PCB) equipped with ICs may be disposed beneath the display panel 201. Optionally, a transparent touchscreen panel (e.g., capacitive touchscreen) may be disposed between the cover glass 202 and the display panel 201, or the layer that detects touch may be integrated into the display panel 201, rather than overlaid on top of it.

The display panel 201 (shown in FIG. 2) forms images by receiving electric signals, e.g., from the graphics sub-system 106. The images generated by the display panel 201 are visible on the display screen 101. The display panel 201 can 40 be of any applicable known or convenient type, including, but not limited to, liquid-crystal displays, micro-LED displays, and organic light-emitting devices.

As illustrated in FIG. 2 and FIG. 3, the printed circuit board 203 may be equipped, inter alia, with the graphics sub-system 106 (e.g., a GPU), an ear speaker 303, a front camera module 301 (including the lens 102), and optical sensors and emitters 104 (e.g., proximity sensor, light sensor, LED indicator, or IR-LED). Dotted lines illustrate the light path 302 of the front-facing camera 301, 102 and the light path 302 of the optical sensors and emitters 104.

In FIG. 2 and FIG. 3, the remaining casing of the smartphone 100 (e.g., lower part, bottom side) is indicated as a dotted line. More information about the assembly of a smartphone 100 may be found in patent application US2014/ 55 0135071 A1, titled "Mobile terminal." More information about a camera module may be found in patent application US2015/0077629 A1, titled "Camera module." More information about a proximity sensor may be found in U.S. Pat. No. 8,996,082 B2, titled "Proximity sensor arrangement having a cold mirror in a mobile device."

FIG. 4 (labeled "prior art") is a diagrammatic representation of the computer system 400 of the smartphone 100. The computer system 400, as known from the prior art, may consist of a processor 401 (CPU), a main memory 402 (RAM), at least one non-volatile memory 403 (e.g., flash memory, SSD, or memory card), an I/O interface 404, including network interface and sensors (e.g., WiFi®,

mobile communications, and accelerometer), and other familiar devices. The components of the computer system **400** can be coupled together via a bus system **405** or through some other known or convenient devices.

Instructions 406 for the execution on the processor 401 5 and data (e.g., text data, vector data, and bitmap image data) may be stored in the main memory 402 and/or the nonvolatile memory 403. For example, the processor 401 may execute instructions 406 (stored in main memory 402 and/or non-volatile memory 403) to process bitmap image data 10 (also stored in main memory 402 and/or non-volatile memory 403) that is displayed on the display screen 101 via the graphics sub-system 106.

The common computer system **400**, as per FIG. **4**, is intended to illustrate a hardware platform on which any of 15 the subsequent embodiments (and any other components described in this specification) can be implemented. It is to be expressly noted that the computer system **400** integrated into the mobile electronic device (e.g., smartphone **100**) can be of any applicable known or convenient type. 20

Turning now to the embodiments of the present invention, FIG. **5** shows the front side of an exemplary smartphone **100** (or phablet) with a display screen **101** and at least one front camera (lens **102**), optical sensor **104**, and/or optical emitter **104**. The smartphone **100** and the display screen **101** can 25 have a different (e.g., larger) aspect ratio, as indicated by curved break lines and associated curly brackets in the drawings.

In the example, as per FIG. 5, the housing of the smartphone 100 is characterized by a very thin border 502, 105 at 30 the upper edge, lower edge, left edge, and right edge of the display screen 101. In particular, the border 502 at the top of display screen 101 may be very thin. The benefits are, inter alia, a bigger screen and/or smaller phone dimensions. In order to accommodate the lens 102 of a front camera 35 module, optical sensor 104, and/or optical emitter 104 at the top of the display screen 101-in spite of the very thin border 502-the upper left-hand and right-hand corners of the display screen 101 are cut out. This is illustrated in FIG. 5: A recess or cutout 501 at the top left-hand corner and a 40 recess or cutout 501 at the top right-hand corner have been removed from the display panel. For illustrative purposes, the display screen 101, as shown in FIG. 5, is emphasized by means of standard drafting symbol patterns. The color "dark gray" of the display screen 101 could represent the display 45 panel in the switched-off state.

As shown in FIG. 5, at least one lens 102 of a front camera module, optical sensor, and/or optical emitter may be located at least in the upper right-hand corner of the housing of the smartphone 100, at the location of the cutout 501. Both the 50 display 101 and the lens 102 in the upper right-hand corner may be covered by a transparent (or semi-transparent) material, such as glass, as illustrated in the drawings by means of shading lines slanted at an angle of 45 degrees.

Depending on the embodiment, one or more cutouts **501** 55 of the display screen **101** may have mainly a convex shape (as opposed to a conventional display screen with rounded corners, which has concave cutouts). As can be seen in FIG. **5**, a cutout **501** that is mainly convex may be advantageous because it maximizes the remaining area of the display 60 screen **101**, while still accommodating the lens **102** of the front-facing camera (or other optical sensors/emitters **104**).

FIG. 6 shows a perspective view of an embodiment of the smartphone 100 featuring very thin borders 502, 105 (at least at the upper edge, left edge, and right edge of the 65 display screen 101) and cutouts 501 at the top left and right corners of the display screen 101. The lens 102 of a front

8

camera module and/or other optical sensors/emitters 104 may be disposed at the locations of the cutouts 501. For illustrative purposes, the display screen 101 displays the self-portrait of a woman that may have been taken by the front camera via the lens 102. FIG. 7 shows the rear side of the smartphone 100, and FIG. 8, FIG. 9, and FIG. 10 show side views of the smartphone 100, as an example.

Turning now to FIG. 11, the front side of an exemplary smartphone 100 with thin borders 502, 105 is shown, ¹⁰ wherein the lens 102 (e.g., of a front camera module) is located in the upper left-hand corner at a first cutout 501 of the display screen 101. A second cutout 501 (that may accommodate optical sensors 104 and/or optical emitters 15 104) is located in the upper right-hand corner of the display screen 101. As specifically shown in FIG. 11, the display screen 101 displays an uninterrupted status bar 1101 that extends—without interruptions—from the first cutout 501 (in the upper left-hand corner) to the second cutout 501 (in 20 the upper right-hand corner).

As can be seen in FIG. 11, the upper status bar 1101 between the two cutouts 501 may contain information such as the signal strength (icon for signal strength: "four bars" in the present example), the time of day ("10:30 AM" in the present example), and the battery level (icon for the battery: "83%" in the present example). It can also be seen that the upper status bar 1101 is not interrupted by a notch in the middle of the upper edge of the display screen 101, i.e., if desired, information such as the time of day ("10:30 AM" in the example) may be positioned in the middle of the status bar 1101 without being hidden by a notch. The status bar 1101 may display any suitable order.

As is conventional for a smartphone 100, the screen content displayed on the display screen 101 may change, i.e., may switch to a different screen content. The example, as per FIG. 12, shows a display screen 101 (with two cutouts 501) that displays a letterboxed wide-screen movie frame 1201 (e.g., black bars 1202 above and below the movie 1201). As can be seen in the drawing, the wide-screen movie 1201 is displayed as a full screen in the landscape mode, i.e., the user may hold the smartphone 100 horizontally.

The wide-screen movie **1201** may have an aspect ratio that is wider, i.e., greater, than the aspect ratio of the display screen **101**. Therefore, the wide-screen movie **1201** may be displayed in "letterbox" mode, such that the two cutouts **501** of the display screen **101** are mostly located in the region of the horizontal bars **1202** above and below the wide-screen movie **1201**, thereby reducing or preventing the problem that parts of the movie **1201** are invisible (i.e., hidden) due to the cutouts **501**. Depending on the aspect ratio, the wide-screen movie **1201** may be completely visible—no corners of the movie **1201** may be hidden by the cutouts **501**.

As specifically shown in FIG. 12, the wide-screen movie frame 1201 uses the full width of the display screen 101 (in landscape orientation) and there is no notch in the middle of the left edge of the display screen 101 that would hide a part of the movie 1201 on the left. Moreover, the embodiment, as per FIG. 12, is able to display the movie 1201 in a larger manner than a conventional smartphone (with the same dimensions of the casing).

The cutout(s) **501**, the lens **102**, and/or the optical sensor(s)/emitter(s) **104** may be located at any corner(s) of the display screen **101**, for example, at all four corners of the display screen **101** (as shown in FIG. **13** and FIG. **14**), in two corners (as shown in FIG. **11** and FIG. **12**), or in one corner only.

FIG. 13 shows the front side of an embodiment of a smartphone 100 that features thin borders 502 at the upper and lower edge, thin borders 105 at the left and right edge, and cutouts 501 at all four corners of the display screen 101. The lens 102 of a front camera module and/or other optical 5 sensors/emitters 104 may be disposed at the locations of all four cutouts 501. The display screen 101 displays a status bar 1101 between the two upper cutouts 501. Furthermore, the display screen 101 shows schematized app icons of a start screen (illustrated in dotted lines). 10

A letterboxed wide-screen movie **1201** may also be displayed by a display screen **101** having cutouts **501** at all four corners—without hiding significant parts of the movie **1201**. As can be seen in FIG. **14**, a wide-screen movie frame **1201** (illustrated in dotted lines) is displayed in landscape mode 15 using the full width of the display screen **101** both at the left and right side (horizontal orientation). All four cutouts **501** may be located in the region of the horizontal bars **1202** above and below the wide-screen movie **1201** either entirely or for the most part—depending on the aspect ratio of the 20 wide-screen movie **1201**. The thin borders **502** at the left and right side of the smartphone's casing **100** (orientated horizontally) maximize the size of the movie **1201**.

FIG. 15 shows the front side of a further embodiment of the smartphone 100 featuring thin borders 105, 502 at all 25 edges and cutouts 501 (for optical sensors/emitters 102, 104) at all four corners of the display screen 101. In this example, the display screen 101 displays a status bar 1101 at the top, onscreen soft keys 1501 for the navigation at the bottom, and the chat dialog of a communication app. 30

As is specifically shown in FIG. **15**, the horizontal navigation bar **1501** extends—without interruptions—from a first cutout **501** in the lower left-hand corner to a second cutout **501** in the lower right-hand corner and comprises onscreen soft keys, such as "Back" (arrow icon), "Home" 35 (house icon), or "Menu" (menu icon).

In embodiments of the present invention, the cutouts **501** of the display screen **101** and the corners of the smartphone's housing **100** may have any suitable shape. FIG. **16** through FIG. **21** illustrate various exemplary shapes of 40 cutouts **501**, including, but not limited to, a rectangle with rounded corners (see enlarged view **1600** and **1700**), a curved shape, (see enlarged view **1800** and **1900**), or a rectangle with sharp corners (see enlarged view **2000** and **2100**). For illustrative purposes, the display screen **101**, as 45 shown in the enlarged views, is emphasized by means of standard drafting symbol patterns (color "dark gray").

Furthermore, in embodiments of the present invention, the status bar **1101** between the two upper cutouts **501** and the navigation bar **1501** between the two lower cutouts **501** may 50 have any suitable height. This is illustrated in the non-limiting example, as per FIG. **22**. As can be seen by means of the dot-dash auxiliary lines, the height of the icons of the status bar **1101** may be smaller than the height of the cutout(s) **501**, and the height of the icons of the navigation 55 bar **1501** may be greater than the height of the cutout(s) **501**.

Turing now to FIG. 23, the display screen 101 of an exemplary smartphone 100 displays the self-portrait of a woman that may have been taken by the front camera. Furthermore, the display screen 101 displays a schematized 60 camera lens symbol 2301, which may be animated and which may indicate an active front camera. In other words, when taking a self-portrait photograph ("selfie") with the front-facing camera (lens 102), the status of the front camera may be indicated on the display screen 101 by means of a 65 quarter circle 2301 or one or more circular sections 2301 that surround the lens 102—as shown in FIG. 23. The quarter

10

circle or circular sections 2301 may be animated and may indicate operating states of the front camera, such as "active."

With reference to FIG. 12, FIG. 14, and FIG. 23, it should be noted that the status bar 1101 may not be displayed on the display screen 101 (i.e., hidden or faded out) in these cases, in order to improve the visual representation of the displayed screen content, such as a maximized screen width for the wide-screen movie 1201 (in FIG. 12 and FIG. 14) or to display a quarter circle 2301 that surrounds the lens 102 (in FIG. 23).

Instead of a flat display screen 101, as shown in FIG. 6, FIG. 10, and FIG. 23, all embodiments may be designed with a slightly curved display screen 101, i.e., a display having a curved surface. Such an embodiment is shown in FIG. 24 through FIG. 27 for the purpose of example only, wherein FIG. 24 shows the rear side of the smartphone 100 and FIG. 25, FIG. 26, and FIG. 27 show side views of the smartphone 100. The curved display screen 101 is visible in FIG. 27. Furthermore, FIG. 24 shows a rear side of the smartphone 100 that is characterized by a fully symmetrical arrangement. For example, a rear camera may be located both at the top and at the bottom of the rear side.

In the claims, the term "horizontal matte region" is used for the horizontal bar(s) **1202** above and/or below the wide-screen movie **1201**. The borders **105**, **502** (or "thin borders," as used in the claims) that surround the display screen **101** shall be defined as the distance between the outer housing frame of the smartphone **100** and the beginning of the active screen area (which displays the screen content). Furthermore, the term "screen content" (or "first screen content," "second screen content," etc., as used in the claims) shall be interpreted as the entire, all-encompassing content displayed on the display screen **101**.

The conjunction "or," as used in the claims, shall be interpreted as an alternative between two (or more) features, such as alternative embodiments, and shall not be construed to specifically exclude any "non-selected" feature (such as an "XOR" operator). A list of features connected with an "or" that starts with the phrase "at least" or that ends with the phrase "a combination thereof" covers both single features from the list as well as any groups of features thereof. Furthermore, the conjunction "or," as used in the claims, shall not be construed as a logical "OR" operator of a computer program: even if a claim contains a condition, the conjunction "or" is intended to specify alternative features of the claim, such as alternative method steps.

Although the description above contains many specificities, these should not be construed as limiting the scope of the embodiments but as merely providing illustrations of some of several embodiments. Thus, the scope of the embodiments should be determined by the appended claims and their legal equivalents, rather than by the examples given.

What is claimed is:

1. A method for maximizing the size of a wide-screen movie in relation to the outer dimensions of a smartphone equipped with a front camera, comprising:

a) providing an oblong display, said display being aligned in landscape orientation and having a left edge, a right edge, an upper edge, a lower edge, a horizontal screen width, an upper-left corner, and a lower-left corner, wherein said display has an upper-left cutout at said upper-left corner and a lower-left cutout at said lowerleft corner, said upper-left cutout having an upper-left cutout area, and said lower-left cutout having a lowerleft cutout area,

- b) providing at least one front camera and at least one optical emitter,
- c) providing an oblong casing with at least a first thin border and a second thin border, said casing being aligned in landscape orientation and having an outer 5 horizontal measurement,
- d) configuring said smartphone to display a first screen content on said display, comprising:
 - i) a wide-screen movie in landscape orientation that seamlessly extends over the entire horizontal screen 10 width of said display, said wide-screen movie having a left side, a right side, and an image width, wherein the left side of said wide-screen movie is displayed between said upper-left cutout and said lower-left cutout, 15
 - ii) an upper horizontal matte region located above said wide-screen movie, wherein said upper horizontal matte region extends into said upper-left cutout area, such that said upper-left cutout is accommodated, at least in part, in said upper horizontal matte region, 20
 - iii) a lower horizontal matte region located below said wide-screen movie, wherein said lower horizontal matte region extends into said lower-left cutout area, such that said lower-left cutout is accommodated, at least in part, in said lower horizontal matte region, 25
- e) disposing said at least one front camera, at least in part, in said upper-left cutout area or said lower-left cutout area, and disposing said at least one optical emitter, at least in part, in said lower-left cutout area or said upper-left cutout area, 30
- f) disposing said first thin border adjacent to the left side of said wide-screen movie and said second thin border adjacent to the right side of said wide-screen movie, such that the outer horizontal measurement of said casing is nearly equal to the image width of said 35 wide-screen movie,
- g) configuring said smartphone to alternately display a second screen content on said display, comprising:
 - i) a photograph having a visible area, wherein said photograph seamlessly extends to the left edge, the 40 right edge, the upper edge, and the lower edge of said display, and
 - ii) a schematized camera lens symbol located adjacent to said upper-left cutout area or said lower-left cutout area, wherein said schematized camera lens symbol 45 surrounds said upper-left cutout area or said lowerleft cutout area substantially in a quarter circle, such that the visible area of said photograph is maximized, said schematized camera lens symbol being animated and being visible, at least if said front 50 camera is active.

2. The method of claim 1, wherein said upper horizontal matte region and said lower horizontal matte region are empty and contain no content.

3. The method of claim **2**, wherein said upper horizontal 55 matte region and said lower horizontal matte region are displayed in black.

4. The method of claim 1, wherein said display has a curved surface.

5. The method of claim **1**, wherein said smartphone is a 60 phablet.

6. A method for increasing the screen area for a widescreen movie in relation to the outer dimensions of a smartphone equipped with a front camera, comprising:

a) providing an oblong display, said display being aligned 65 in landscape orientation and having a left edge, a right edge, an upper edge, a lower edge, a horizontal screen width, at least an upper corner, and at least a lower corner, wherein said display has an upper cutout at said upper corner and a lower cutout at said lower corner, said upper cutout having an upper cutout area, and said lower cutout having a lower cutout area,

- b) providing at least one front camera and disposing said front camera, at least in part, in said upper cutout area or said lower cutout area,
- c) providing an oblong casing with at least a first thin border and a second thin border, said casing being aligned in landscape orientation and having an outer horizontal measurement,
- d) configuring said smartphone to display a first screen content on said display, comprising:
 - i) a wide-screen movie in landscape orientation that seamlessly extends over the entire horizontal screen width of said display, said wide-screen movie having a left side, a right side, and an image width, wherein said wide-screen movie is displayed horizontally between said upper cutout and said lower cutout,
 - ii) an upper horizontal matte region located above said wide-screen movie, wherein said upper horizontal matte region extends into said upper cutout area, such that said upper cutout is accommodated, at least in part, in said upper horizontal matte region,
 - iii) a lower horizontal matte region located below said wide-screen movie, wherein said lower horizontal matte region extends into said lower cutout area, such that said lower cutout is accommodated, at least in part, in said lower horizontal matte region,
- e) disposing said first thin border adjacent to the left side of said wide-screen movie and said second thin border adjacent to the right side of said wide-screen movie, such that the outer horizontal measurement of said casing is nearly equal to the image width of said wide-screen movie,
- f) configuring said smartphone to alternately display a second screen content on said display, comprising:
 - a photograph having a visible area, wherein said photograph seamlessly extends to the left edge, the right edge, the upper edge, and the lower edge of said display, and
 - ii) a schematized camera lens symbol located adjacent to said upper cutout area or said lower cutout area, wherein said schematized camera lens symbol surrounds said upper cutout area or said lower cutout area substantially in a quarter circle, such that the visible area of said photograph is maximized, said schematized camera lens symbol being animated and being visible, at least if said front camera is active.

7. The method of claim 6, wherein said front camera is a front camera module with at least one lens.

8. The method of claim **6**, wherein said upper horizontal matte region and said lower horizontal matte region are empty and contain no content.

9. The method of claim 6, wherein said display has a curved surface.

10. The method of claim 6, wherein said smartphone is a phablet.

11. A smartphone having a front-facing camera, said smartphone being made for maximizing the size of a wide-screen movie in relation to the outer dimensions of said smartphone, comprising:

a) an oblong display, said display being aligned in landscape orientation and having a horizontal screen width, at least an upper corner, and at least a lower corner, wherein said display has an upper cutout at said upper corner and a lower cutout at said lower corner, said upper cutout having an upper cutout area, and said lower cutout having a lower cutout area,

b) a computer system configured to be at least able to alternately display a first screen content and a second ⁵ screen content on said display,

c) said first screen content comprising:

- i) a wide-screen movie in landscape orientation that seamlessly extends over the entire horizontal screen width of said display, said wide-screen movie having ¹⁰ a left side, a right side, and an image width, wherein said wide-screen movie is displayed horizontally between said upper cutout and said lower cutout,
- ii) an upper horizontal matte region located above said wide-screen movie, wherein said upper horizontal matte region extends into said upper cutout area, such that said upper cutout is accommodated, at least in part, in said upper horizontal matte region,
- iii) a lower horizontal matte region located below said wide-screen movie, wherein said lower horizontal matte region extends into said lower cutout area, such that said lower cutout is accommodated, at least in part, in said lower horizontal matte region,
- d) at least one front camera module with at least one lens 25 disposed, at least in part, in said upper cutout area or said lower cutout area, and at least one optical emitter disposed, at least in part, in said lower cutout area or said upper cutout area,
- e) an oblong casing with at least a first thin border and a second thin border, said casing being aligned in landscape orientation and having an outer horizontal measurement, wherein said first thin border is disposed adjacent to the left side of said wide-screen movie and said second thin border is disposed adjacent to the right side of said wide-screen movie, such that the outer horizontal measurement of said casing is nearly equal to the image width of said wide-screen movie.
- f) said second screen content comprising:
 - i) an image having a visible area, and
 ii) a schematized camera lens symbol located adjacent
 to said upper cutout area or said lower cutout area,
 wherein said schematized camera lens symbol surrounds said upper cutout area or said lower cutout
 area substantially in a quarter circle, such that the
 visible area of said image is maximized, said schematized camera lens symbol being animated and
 being visible, at least if said front camera module is active.

12. The smartphone of claim **11**, wherein said upper $_{50}$ horizontal matte region and said lower horizontal matte region are empty and contain no content.

13. The smartphone of claim 12, wherein said upper horizontal matte region and said lower horizontal matte region are displayed in black.

14. The smartphone of claim 11, wherein said display has a curved surface.

15. The smartphone of claim **11**, wherein said smartphone is a phablet.

14

- **16**. A smartphone comprising:
- a) an oblong display, said display being aligned in landscape orientation and having a horizontal screen width, at least an upper corner, and at least a lower corner, wherein said display has an upper cutout at said upper corner and a lower cutout at said lower corner, said upper cutout having an upper cutout area, and said lower cutout having a lower cutout area,
- b) at least one front camera disposed, at least in part, in said upper cutout area or said lower cutout area,
- c) a computer system configured to be at least able to alternately display a first screen content and a second screen content on said display,
- d) said first screen content comprising:
 - i) an image having a visible area, and
 - ii) a schematized camera lens symbol located adjacent to said upper cutout area or said lower cutout area, wherein said schematized camera lens symbol surrounds said upper cutout area or said lower cutout area substantially in a quarter circle, such that the visible area of said image is maximized, said schematized camera lens symbol being animated and being visible, at least if said front camera is active, waid second screen content comprising:
- e) said second screen content comprising:
 - i) a wide-screen movie in landscape orientation that seamlessly extends over the entire horizontal screen width of said display, said wide-screen movie having a left side, a right side, and an image width, wherein said wide-screen movie is displayed horizontally between said upper cutout and said lower cutout,
 - ii) an upper horizontal matte region located above said wide-screen movie, wherein said upper horizontal matte region extends into said upper cutout area, such that said upper cutout is accommodated, at least in part, in said upper horizontal matte region,
 - iii) a lower horizontal matte region located below said wide-screen movie, wherein said lower horizontal matte region extends into said lower cutout area, such that said lower cutout is accommodated, at least in part, in said lower horizontal matte region,
- f) an oblong casing with at least a first thin border and a second thin border, said casing being aligned in landscape orientation and having an outer horizontal measurement, wherein said first thin border is disposed adjacent to the left side of said wide-screen movie and said second thin border is disposed adjacent to the right side of said wide-screen movie, such that the outer horizontal measurement of said casing is nearly equal to the image width of said wide-screen movie.

17. The smartphone of claim 16, wherein said front camera is a front camera module with at least one lens.

18. The smartphone of claim 16, wherein said upper horizontal matte region and said lower horizontal matte region are empty and contain no content.

19. The smartphone of claim **16**, wherein said display has a curved surface.

20. The smartphone of claim **16**, wherein said smartphone is a phablet.

* * * * *