



US010459481B2

(12) **United States Patent**
Pantel

(10) **Patent No.:** **US 10,459,481 B2**

(45) **Date of Patent:** ***Oct. 29, 2019**

(54) **MOBILE DEVICE WITH FRONT CAMERA
AND MAXIMIZED SCREEN SURFACE**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **Lothar Pantel**, Neckargemuend (DE)

8,996,082 B2 3/2015 Tam
9,405,391 B1 8/2016 Mackraz
(Continued)

(72) Inventor: **Lothar Pantel**, Neckargemuend (DE)

(73) Assignee: **inodyn NewMedia GmbH**,
Neckargemuend (DE)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

EM 004013787-0001 S 7/2017
EM 004494417-0001 S 11/2017

This patent is subject to a terminal dis-
claimer.

OTHER PUBLICATIONS

(21) Appl. No.: **16/022,629**

Lothar Pantel, Jul. 3, 2017, "Front-facing camera and maximized
display screen of a mobile device," Early publication of UK patent
application GB1710466.2, published by the inventor/applicant of
the present application, Available online from: <http://www.earlypublication.com>.

(22) Filed: **Jun. 28, 2018**

(65) **Prior Publication Data**

US 2018/0307270 A1 Oct. 25, 2018

(Continued)

(30) **Foreign Application Priority Data**

Primary Examiner — Shan E Elahi

Jun. 29, 2017 (GB) 1710466.2

(51) **Int. Cl.**

G06F 1/16 (2006.01)

G09G 3/20 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **G06F 1/1605** (2013.01); **G02F 1/1338**
(2013.01); **G06F 1/1626** (2013.01);

(Continued)

(58) **Field of Classification Search**


CPC G06F 1/1605; G06F 1/1637; G06F 1/1626;
G06F 3/041; G06F 3/0416; G06F 1/1686;

(Continued)



(57) **ABSTRACT**




A mobile electronic device, for example a smartphone, may
feature thin or curved borders at the left, right, top, and/or
bottom edge of the display screen. To accommodate front-
facing optical sensor(s) and/or emitter(s) despite a border
that is too thin (e.g., too thin for a front camera module and
lens), two or more corners of the display panel have a cutout,
and the optical sensor(s) and/or emitter(s) are disposed, at
least in part, in the areas of these cutouts at the corners. The
cutouts may have a convex shape for the most part, thereby
maximizing the remaining screen area. At least one embodi-
ment of the mobile electronic device may have a display
panel with at least three curved edges, a maximized screen
surface, and minimized outer dimensions.

19 Claims, 34 Drawing Sheets



- (51) **Int. Cl.**
H04M 1/02 (2006.01)
G02F 1/1333 (2006.01)
G06F 3/041 (2006.01)
H01L 27/32 (2006.01)
- (52) **U.S. Cl.**
CPC **G06F 1/1637** (2013.01); **G06F 1/1686**
(2013.01); **G06F 3/041** (2013.01); **G06F**
3/0416 (2013.01); **G09G 3/2092** (2013.01);
H01L 27/323 (2013.01); **H04M 1/0264**
(2013.01); **H04M 1/0266** (2013.01); **G09G**
2340/04 (2013.01); **G09G 2340/145** (2013.01);
G09G 2354/00 (2013.01); **H04M 2250/12**
(2013.01)
- (58) **Field of Classification Search**
CPC G02F 1/13338; H01L 27/323; H04M
1/0266; H04M 1/0264; H04M 2250/12;
G09G 3/2092; G09G 2354/00; G09G
2340/145; G09G 2340/04
USPC 348/36
See application file for complete search history.
- (56) **References Cited**
U.S. PATENT DOCUMENTS
- D775,597 S 1/2017 Kim et al.
D777,700 S 1/2017 Kwon et al.
D794,004 S 8/2017 Kwon et al.
D798,263 S 9/2017 Kwon et al.
9,958,898 B1 * 5/2018 Shaw G06F 1/1601
D847,128 S * 4/2019 Kim G06F 1/1605
D14/248
10,324,492 B2 * 6/2019 Pantel H01L 27/323
D854,524 S * 7/2019 Choi G06T 5/006
D14/248
10,353,426 B2 * 7/2019 Pantel G06F 1/1686
2006/0284850 A1 12/2006 Tokkonen
2012/0032979 A1 2/2012 Blow et al.
2013/0321309 A1 * 12/2013 Tokutake G06F 3/0488
345/173
2014/0015805 A1 * 1/2014 Kim G06F 3/0421
345/175
2014/0068520 A1 * 3/2014 Missig G06F 3/0482
715/841
2014/0135071 A1 5/2014 Lee et al.
2014/0170397 A1 * 6/2014 Shen B29C 45/1671
428/212
2014/0214429 A1 * 7/2014 Pantel G10L 21/16
704/275
- 2014/0320434 A1 * 10/2014 Pantel G06F 3/017
345/173
2014/0325435 A1 * 10/2014 Jung G06F 3/04845
715/790
2015/0077629 A1 3/2015 Jeong
2015/0179214 A1 * 6/2015 Pantel G11B 20/1252
360/48
2015/0254144 A1 * 9/2015 Pantel G11B 20/1252
360/48
2015/0255114 A1 * 9/2015 Pantel G11B 20/1252
360/48
2015/0255115 A1 * 9/2015 Pantel G11B 20/1252
360/48
2015/0271392 A1 9/2015 Musgrave et al.
2015/0317020 A1 * 11/2015 Watanabe G06F 3/044
345/173
2015/0364109 A1 * 12/2015 Jain G09G 5/006
345/156
2016/0132464 A1 5/2016 Imana
2016/0132470 A1 5/2016 Imana
2016/0155471 A1 * 6/2016 Pantel G11B 20/1252
360/47
2016/0240173 A1 8/2016 Bostick et al.
2016/0313593 A1 10/2016 Grip
2017/0004798 A1 1/2017 Park et al.
2017/0123452 A1 5/2017 Evans, V et al.
2017/0123453 A1 5/2017 Evans, V et al.
2017/0123454 A1 5/2017 Evans, V et al.
2017/0123575 A1 5/2017 Evans, V et al.
2017/0124377 A1 5/2017 Evans, V et al.
2017/0124933 A1 5/2017 Evans, V et al.
2017/0126868 A1 5/2017 Evans, V et al.
2017/0126937 A1 5/2017 Evans, V et al.
2017/0126979 A1 5/2017 Evans, V et al.
2017/0162111 A1 6/2017 Kang et al.
2017/0168463 A1 6/2017 Hong et al.
2017/0270848 A1 * 9/2017 Liu G06F 3/04842
2018/0219987 A1 * 8/2018 Pantel G06F 1/1637
2018/0307269 A1 * 10/2018 Pantel G06F 1/1626
- OTHER PUBLICATIONS**
- Alex Hern, May 30, 2017, "Android co-founder reveals new smartphone to take on Apple and Samsung," The Guardian, Available online from: <https://www.theguardian.com/technology/2017/may/30/essential-phone-android-co-founder-reveals-new-smartphone-apple-samsung>.
Samuel Gibbs, Nov. 10, 2017, "iPhone X review: Apple finally knocks it out of the park," The Guardian, Available online from: <https://www.theguardian.com/technology/2017/nov/10/iphone-x-review-apple-face-id-all-screen-design-home-button>.
- * cited by examiner









FIG. 6






FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19





FIG. 20

**FIG. 21**




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35





FIG. 36









FIG. 38








FIG. 43

1

**MOBILE DEVICE WITH FRONT CAMERA
AND MAXIMIZED SCREEN SURFACE****CROSS-REFERENCE TO RELATED
APPLICATIONS**

This application claims priority from United Kingdom Patent Application No. GB1710466.2, filed Jun. 29, 2017.

TECHNICAL FIELD

The present invention relates to mobile electronic devices and, in particular, to methods and systems that increase the size of a display screen.

BACKGROUND

Common smartphones, phablets, tablet computers, or comparable mobile electronic devices contain a front-facing camera placed on the front side of these mobile electronic devices. The front side of the mobile electronic devices also contains a display screen, using a display technology such as liquid-crystal display (LCD) or active-matrix organic light-emitting diode (AMOLED). The display screen may be oblong, with an aspect ratio of, for instance, 16:9, 2:1, 19.5:9, or 21:9.

The user may orient a mobile electronic device with an oblong display screen horizontally or vertically, which may result in operating modes known as “landscape mode” and “portrait mode,” respectively. The page orientation can also be described with the terms “landscape orientation” and “portrait orientation.” For example, a user may hold a smartphone horizontally (landscape mode) and may watch a video or movie displayed in full screen mode on the display screen.

The front-facing camera of a mobile electronic device may be used for video telephony or to take a self-portrait photograph, commonly known as a “selfie.” In recent years, the resolution on front-facing cameras has increased, and it is likely that the resolution will continue to increase in the future (e.g., from 8 megapixels to 13 megapixels) to enable the user to take “selfies” of the highest quality and record high-quality 4K videos. Therefore, in some embodiments, high-quality camera lenses for the front-facing camera and an undisturbed light path are essential.

Patent applications US2017/0123454 A1, US2017/0123453 A1, and US2017/0123452 A1, titled “Camera integrated into a display,” patent application US2017/0123575 A1, titled “Optical sensors disposed beneath the display of an electronic device,” patent application US2017/0124933 A1, titled “Mobile device with display overlaid with at least a light sensor,” patent applications US2017/0126979 A1 and US2017/0126937 A1, titled “Apparatus and method to maximize the display area of a mobile device,” and patent application US2015/0271392 A1, titled “System and method for coordinating image capture in a camera hidden behind a display device” suggest disposing the front-facing camera beneath the display screen of mobile electronic devices. However, depending on the display technology of the screen (e.g., LCD, OLED, Micro-LED, etc.), small, opaque, or semi-transparent structures that may be necessary for the operation of the display screen may blur or cloud the resulting picture of the front-facing camera because the light path must pass through the display screen. Furthermore, LCD panels often also require removing a diffuser layer to adapt them for use as transparent displays, and the polarizing filters of the LCD panels inherently limit

2

the transmission efficiency of unpolarized light. This may reduce the light sensitivity of a front-facing camera located beneath the display screen, especially in low-light conditions.

SUMMARY

Embodiments of the present invention are directed to mobile electronic devices with a display screen and at least one front-facing optical sensor or optical emitter (e.g., a front-facing camera, an optical image sensor, an IR-LED, or another optical component). Examples of mobile electronic devices are smartphones, phablets, tablet computers, smart-watches, subnotebooks, or laptops. The scope of the embodiments is set forth by means of the features of the independent claims. Advantageous embodiments, alternatives, and optional features are specified in the dependent claims.

In some embodiments, a mobile electronic device features thin borders at the left, right, top, and/or bottom edge of the display screen. To accommodate optical sensor(s) and/or optical emitter(s) in spite of a border that is too thin (e.g., too thin for a front camera module and lens), two or more corners of the display panel have a cutout or recess, and the optical sensor(s) and/or optical emitter(s) are disposed, at least in part, in the areas of these cutouts (at the corners of the display panel). Optionally, the cutouts may have a convex shape for the most part, thereby maximizing the remaining screen area.

For example, a mobile electronic device may have a front-facing optical sensor, a maximized screen surface, and minimized outer dimensions, and may comprise:

- a) a display panel with at least a first cutout at the upper-left corner and a second cutout at the upper-right corner, said display panel having an upper display panel edge, a left display panel edge, and a right display panel edge, wherein:
 - i) said upper display panel edge, located between said first cutout and said second cutout, is bent to the rear of said display panel, so that the outer vertical measurement of said display panel is reduced while keeping the utilizable surface area of said display panel,
 - ii) said left display panel edge, located below said first cutout, and said right display panel edge, located below said second cutout, are bent to the rear of said display panel, so that the outer horizontal measurement of said display panel is reduced while keeping the utilizable surface area of said display panel,
 whereby said first cutout and said second cutout prevent the upper-left corner and the upper-right corner of said display panel from getting crumpled due to the bent upper display panel edge,
- b) at least one front-facing optical sensor disposed, at least in part, in the area of said first cutout or in the area of said second cutout,
- c) a computer system connected to said display panel and said front-facing optical sensor.

The aforementioned and many further aspects, variants, objectives, and advantages of the invention will be comprehensible to those skilled in the art after reading detailed descriptions of the embodiments.

BRIEF DESCRIPTION OF THE DRAWINGS

Further features, advantages, and potential applications will be apparent from the drawings. All described and/or illustrated features, alone or in any combination, indepen-

dent of the synopsis in individual claims, constitute the subject matter of the invention.

FIG. 1 shows a conventional smartphone.

FIG. 2 is a diagrammatic representation of the computer system of the smartphone.

FIG. 3 shows the front side of a first embodiment (upper part of the casing).

FIG. 4 shows a sectional view of the first embodiment of FIG. 3.

FIG. 5 shows another sectional view of the first embodiment of FIG. 3.

FIG. 6 shows further aspects of the front side of the first embodiment.

FIG. 7 is a perspective view of a second embodiment.

FIG. 8 shows the front side of a third embodiment.

FIG. 9 shows the front side of a fourth embodiment.

FIG. 10 shows the front side of a fifth embodiment.

FIG. 11 shows the rear side of the fifth embodiment.

FIG. 12 is a top plan view of the fifth embodiment.

FIG. 13 is a bottom plan view of the fifth embodiment.

FIG. 14 is a side view of the fifth embodiment.

FIG. 15 shows the front side of a sixth embodiment.

FIG. 16 is a perspective view of a seventh embodiment.

FIG. 17 shows a sectional view of the seventh embodiment of FIG. 16.

FIG. 18 is a perspective view of an eighth embodiment.

FIG. 19 shows the front side of a ninth embodiment.

FIG. 20 is a flowchart used by embodiments of the present invention.

FIG. 21 is another flowchart used by embodiments of the present invention.

FIG. 22 is a flowchart showing further aspects of the present invention.

FIG. 23 shows screen objects displayed on a display panel.

FIG. 24 shows screen objects changed in position and size.

FIG. 25 shows screen objects reduced in size and shifted diagonally.

FIG. 26 shows an e-book.

FIG. 27 shows an e-book with an adjusted length of the text lines.

FIG. 28 shows a scrollable HTML web page or an e-book/app with scrollable pages.

FIG. 29 shows the HTML web page (or e-book/app) scrolled down by one line.

FIG. 30 shows a scrollable screen content with text lines and pictures.

FIG. 31 shows the screen content of FIG. 30 scrolled down by a few lines.

FIG. 32 shows an embodiment with an uninterrupted status bar at the top.

FIG. 33 shows an approach how to maximize the size of a wide-screen movie.

FIG. 34 is another example of the approach shown in FIG. 33.

FIG. 35 is yet another example of the approach shown in FIG. 33.

FIG. 36 shows an embodiment with a status indicator (quarter circle) next to the front camera.

FIG. 37 shows an embodiment with a computer game and acoustic emitters at all four corners.

FIG. 38 is a perspective view of a further embodiment with curved edges.

FIG. 39 is a top plan view of the embodiment of FIG. 38.

FIG. 40 is a front elevation view of the embodiment of FIG. 38.

FIG. 41 is a right side elevation view of the embodiment of FIG. 38.

FIG. 42 shows an embodiment with a mechanical keyboard below the display screen.

FIG. 43 shows a foldable smartphone.

DETAILED DESCRIPTION

FIG. 1 shows a conventional smartphone **100** as an example of a mobile electronic device. The drawing illustrates a display screen **101** with touchscreen functionality, the lens **102** of a front-facing camera, an earpiece **103** (speaker for telephone calls), a combined proximity and light sensor **104**, and an LED indicator **105** (e.g., on/off state of the smartphone **100**, charging of the battery). A graphics sub-system **108** (integrated into the device **100** and shown in dotted lines in FIG. 1) is responsible for generating the screen content displayed on the display screen **101**.

As can be seen in FIG. 1, conventional smartphones **100** typically feature a thin border **106** at the left edge of the display screen **101** and a thin border **107** at the right edge of the display screen **101**. It can also be seen that in the example of FIG. 1, a wide border is required, at least at the top of the front side of the smartphone **100**, to accommodate the lens **102** (front camera), the earpiece **103** (for the ear speaker), the proximity/light sensor **104**, and the LED indicator **105**.

FIG. 2 is a diagrammatic representation of the computer system **200** of the smartphone **100** or a similar device (e.g., tablet computer, smartwatch, or game console). The computer system **200** may consist of a processor **201** (CPU), a main memory **202** (RAM), at least one non-volatile memory **203** (e.g., flash memory, SSD, or memory card), an I/O interface **204**, a network interface (e.g., WiFi®, mobile communications), sensors and emitters (e.g., proximity sensor, camera, accelerometer, loudspeaker, LEDs, etc.), a display screen **101** with touchscreen functionality, and other familiar devices. The components of the computer system **200** can be coupled together via a bus system **205** or through some other known or convenient devices.

Instructions **206** for the execution on the processor **201** and data (e.g., text data, vector data, and bitmap image data) may be stored in the main memory **202** and/or non-volatile memory **203**. For example, the processor **201** may execute instructions **206** (stored in main memory **202** and/or non-volatile memory **203**) to process bitmap image data (also stored in main memory **202** and/or non-volatile memory **203**) that is displayed on the display screen **101** via the graphics sub-system **108**. The main memory **202** and/or non-volatile memory **203** may contain, inter alia, sensor processing instructions, media processing instructions, and other instructions that are required for the tasks described below. Touchscreen input (e.g., a gesture for scrolling a page) may be detected by the touchscreen of the display screen **101** and may be reported to the processor **201** via the bus system **205**.

The computer system **200**, as per FIG. 2, is intended to illustrate a hardware platform on which any of the subsequent embodiments (and any other components described in this specification) can be implemented. It is to be expressly noted that the computer system **200** integrated into the mobile electronic device (e.g., smartphone **100**) can be of any applicable known or convenient type.

FIG. 3 through FIG. 6 show a first embodiment in accordance with the present invention. FIG. 3 shows the front side of the upper part of a smartphone **100**. FIG. 4 shows a sectional view of the smartphone **100** taken at the

5

sectioning plane and in the direction indicated by section line 4-4 (in FIG. 3). Another sectional view of the smartphone 100 is shown in FIG. 5, which is taken at the sectioning plane indicated by section line 5-5. FIG. 6 is a view of the front side of the smartphone 100 showing further aspects of the first embodiment. As indicated by curved break lines, the smartphone 100 and the display screen 101 can have a different, e.g., larger, aspect ratio. For instance, the display screen 101 may have an aspect ratio of 16:9, 21:9, 2:1, 3:1, etc.

Referring to the sectional views shown in FIG. 4 and FIG. 5, the smartphone 100 may consist of several layers: the front side of the casing of the smartphone 100 may consist of a cover glass 405. An oblong display panel 401 may be disposed beneath the cover glass 405, and a printed circuit board 404 (PCB) equipped with ICs may be disposed beneath the display panel 401. Optionally, a transparent touchscreen panel (e.g., capacitive touchscreen) may be disposed between the cover glass 405 and the display panel 401, or the layer that detects touch may be integrated into the display panel 401, rather than overlaid on top of it. As illustrated in FIG. 4 and FIG. 5, the printed circuit board 404 may be equipped, inter alia, with a graphics sub-system 108 (e.g., a GPU), a front camera module 402 (e.g., with a CCD or CMOS sensor), a proximity/light sensor 104, an LED 105, and an ear speaker 403. The ear speaker 403 may be of any applicable known or convenient type, including piezo-electric speakers.

In FIG. 4 and FIG. 5, the remaining casing of the smartphone 100 (e.g., rear side) is indicated as a dotted line. More information about the assembly of a smartphone 100 may be found in patent application US2014/0135071 A1, titled "Mobile terminal." More information about a camera module may be found in patent application US2015/0077629 A1, titled "Camera module." More information about a proximity sensor may be found in U.S. Pat. No. 8,996,082 B2, titled "Proximity sensor arrangement having a cold mirror in a mobile device."

The display panel 401 (shown in FIG. 4 through FIG. 6) forms images by receiving electric signals (e.g., from the graphics sub-system 108). The images generated by the display panel 401 are visible on the display screen 101. It is to be expressly noted that the display panel 401 can be of any applicable known or convenient type, including, but not limited to, liquid-crystal displays, micro-LED displays, and organic light-emitting devices.

For example, the display panel 401 may be an LC panel. The LC panel may include a thin film transistor (TFT) substrate, a color filter substrate, and LC molecules injected between the TFT substrate and the color filter substrate. The TFT substrate may include gate lines and data lines implemented as matrices. Thin film transistors (TFTs) may be formed at crossing points of the gate lines and the data lines. A signal voltage is applied to a common electrode disposed between a pixel electrode and the color filter substrate. Liquid crystal molecules are aligned between the pixel electrode and the common electrode according to the signal voltage, thereby controlling light transmittance. The color filter substrate may include a color filter and a common electrode, the color filter having red, green, and blue filters repeatedly formed in a state in which black matrices are disposed therebetween. The common electrode may be formed of a transparent conductive material such as indium tin oxide (ITO) or indium zinc oxide (IZO).

A pair of polarizers may be arranged on the upper and lower surfaces of the LC panel. The polarizers may be arranged to cross each other. The polarizer disposed under

6

the LC panel serves to polarize light incident onto the LC panel, and the polarizer formed on the LC panel serves as an analyzer. A backlight unit may be disposed beneath the LC panel. The backlight unit may include a diffusion sheet, reflection sheet, and prism sheet.

Alternatively, the display panel 401 may be implemented as an active-matrix OLED display consisting of several layers, e.g., cathode layer, organic active layers, thin-film transistor (TFT) array, and substrate. An active matrix of OLED pixels generates light (luminescence) upon electrical activation. The active matrix of OLED pixels may be deposited or integrated onto the thin-film transistor (TFT) array, which functions as a series of switches to control the current flowing to each individual pixel. Known TFT back-plane technologies, such as polycrystalline silicon (poly-Si) and amorphous silicon (a-Si), may be used. More information may be found in patent application US2017/0162111 A1, titled "Display Apparatus." Optionally, the display panel 401 may have an in-cell touch panel that integrates a capacitive sensor array.

Referring to FIG. 3, the housing of the smartphone 100 is characterized by a thin edging or border 301, 106, 107 at the upper edge, left edge, and right edge of the display screen 101. In particular, in the present example, the border 301 at the top of the display screen 101 is very thin. The benefits are, inter alia, a bigger screen and/or smaller phone dimensions. For example, the borders 301, 106, 107 may have a width of 4 mm, 2 mm, 1.5 mm, 1 mm, 0.5 mm, or less. Optionally, each border 301, 106, 107 may have a different width. The first embodiment features an earpiece 103 (for the ear speaker 403 shown in FIG. 4) that is a long, narrow gap. For example, the gap of the earpiece 103 may have a width of 1 mm, 0.5 mm, or less.

In order to accommodate optical sensors/emitters and/or the lens 102 of the front-facing camera—in spite of the very thin border 301 at the top of the display screen 101—the upper left-hand and right-hand corners of the display panel 401 each have a cutout 601. This is illustrated in FIG. 6 as an example: A cutout 601 at the top left-hand corner and a cutout 601 at the top right-hand corner have been "removed" from the display panel 401. In the present example, the cutouts 601 at the corners of the display panel 401 have a convex shape as opposed to a conventional display screen with rounded corners (which have concave cutouts). Cutouts 601 that have mainly a convex shape may be advantageous, because this maximizes the remaining area of the display panel 401 while still accommodating the lens 102 of the front-facing camera (and/or other sensors/emitters). For illustrative purposes, the display panel 401, as shown in FIG. 6, is emphasized by means of standard drafting symbol patterns. The depicted drafting symbol pattern "gray" (or "dark gray") of the display panel 401 could represent the display screen 101 in the switched-off state.

Referring to FIG. 4, which shows the sectioning plane 4-4 at the top of the display screen 101, the front camera module 402 and affiliated lens 102 are disposed beneath the cover glass 405 at the location of the cutout 601 on the left, such that, in the present example, the front camera module 402 and the lens 102 fill the void at the level of the display panel 401. The dotted line 406 shows the unobstructed light path of the front camera module 402, which must only pass through the cover glass 405. As a result, the camera system (camera module 402 and lens 102) may use the entire height of the casing of the smartphone 100. Depending on the embodiment, this may be advantageous, because, compared to disposing the front-facing camera beneath the display panel 401 (as suggested in the prior art), the length of the

lens system of the camera module **402** can be maximized. The length of a lens system can be a limiting factor for taking high quality pictures, and disposing the front-facing camera beneath the display panel **401** may reduce the maximum length of the lens system by the thickness of the display panel **401**.

With continued reference to the example shown in FIG. 4, the proximity/light sensor **104** and LED indicator **105** are disposed beneath the cover glass **405** at the location of the cutout **601** on the right, such that they fill the void at the level of the display panel **401**, at least partially. Dotted lines **406** show the light paths of the proximity/light sensor **104** and LED indicator **105**.

Both, the display panel **401** and the optical sensors/emitters (lens **102**, proximity/light sensor **104**, LED indicator **105**) may be covered by a continuous transparent material, such as transparent plastic or glass **405**, as shown in FIG. 4 and FIG. 5, for purpose of example only, and indicated in FIG. 3 by means of shading lines slanted at an angle of 45 degrees.

Comparing the sectional views shown in FIG. 4 and FIG. 5, it can be seen that the width of the display panel **401** is reduced at the locations of the cutouts **601**. This is indicated by dot-dash projection lines. Optionally, in other embodiments, only opaque and/or semi-transparent layers of the display panel **401** may be cut out, that is, transparent layers of the display panel **401** may remain. This may depend on the technology used by the display panel **401** (e.g., LC panel or AMOLED).

The front-facing camera (front camera module **402** and lens **102**) and other optical or acoustic sensors and emitters (e.g., proximity/light sensor **104**, LED indicator **105**, flash-light, optical infrared emitter, IR or UV sensor, fingerprint sensor, iris scanner, or sensor(s) for face recognition, face tracking, or eye tracking) may be located in all four corners of the casing of the smartphone **100**, in the two upper corners, in the two lower corners, in the corners on the left or right side of the casing, in diagonally located corners, or in one corner only. Also, the cutout(s) **601** and the casing of the smartphone **100** may have different shapes, i.e., each cutout **601** and the casing may have a shape that is different from the shapes shown in the drawings of the present specification. For example, the shape of the cutouts **601** may vary between a quarter circle (as shown in FIG. 6) and a square or rectangle. In some embodiments, the cutouts **601** may have the shape of a square or rectangle with rounded edges, the shape of a square or rectangle with sharp edges, or any other suitable shape. The following drawings illustrate different locations for sensors and emitters and different shapes of the cutouts **601**, for purpose of example only.

FIG. 7 shows a perspective view of a second embodiment. The second embodiment corresponds to the first embodiment, except that there is a second front-facing camera to support self-portrait photographs (“selfies”) taken in stereoscopic 3D, to record videos in stereoscopic 3D, or to generate other data based on stereoscopic information. (E.g., depth data, bokeh effect, etc.) The lens **701** of the second front-facing camera is located in the upper right-hand corner of the display screen **101**. The width of the casing of the smartphone **100** is suitable for the interaxial separation between the two lenses **102**, **701**. Interaxial separation refers to the distance between the centers of two camera lenses. The interocular separation or interpupillary distance technically refers to the distance between the centers of human eyes.

Alternatively, the second front-facing camera may have a wide-angle lens **701**, or ultra wide angle lens **701**, while the

first front-facing camera may have a “normal” front camera lens **102**. In one non-limiting example, the wide-angle lens **701** may have an angle of view (AOV) of 120 degrees, which may simplify taking “group selfies.” In other embodiments, the second front-facing camera may be used to gain information about the depth of field (DOF), e.g., to generate “selfies” with a background that is out of focus (shallow focus or bokeh effect). In yet another embodiment, the second front-facing camera may be an iris scanner or an infrared camera for face recognition used for unlocking the smartphone **100**.

FIG. 8 shows the front side of a third embodiment in which screen content is displayed on the display screen **101** as an example. Compared to the first embodiment, the lens **102** of the front-facing camera is located in the upper right-hand corner of the display screen **101**. Instead, an electronic flash unit **801** (or another optical emitter) is disposed at the upper left-hand corner of the display screen **101**, at least in part in the area of the cutout **601**. The electronic flash unit **801** may be a flash LED, an electronic flashlamp, or an IR-LED, e.g., to support taking “selfies” in low light conditions. An LED flash or IR-LED can also be used for illumination of video recordings or as an autofocus assist lamp in low light conditions. In other embodiments, a warning light, caution lamp, or anti-theft alert signal may be disposed at the location of the cutout **601** in the upper left-hand corner (or any other corner) of the display screen **101**.

FIG. 9 shows the front side of a fourth embodiment featuring a front-facing camera (lens **102**) in the upper left-hand corner, a light guide **901** (which combines several optical sensors and emitters) in the upper right-hand corner, an ultraviolet (UV) sensor **902** in the lower left-hand corner, and a fingerprint sensor **903** in the lower right-hand corner of the display panel **401**.

Many technologies are known in the prior art for capturing a live scan of the fingerprint pattern, including optical, capacitive, RF, thermal, piezoresistive, ultrasonic, or piezoelectric fingerprint sensors. For example, the fingerprint sensor **903** may be an optical, ultrasonic, or capacitance fingerprint sensor.

The light guide **901** may transmit a light beam between the environment outside and the sensors and emitters inside the smartphone **100**. By this means, the light guide **901** may combine, by way of example, a proximity sensor, a light sensor, an LED indicator (indicating “on,” “off,” and “charging of accumulator”), and a flash LED. The proximity sensor and/or the light sensor may be deactivated or ignored for the short period of time during which the flash LED brightly lights up. A light guide **901** may have the advantage that the visual impression of the upper left-hand corner (lens **102**) and of the upper right-hand corner (light guide **901**) appear similar to the user, because there is only one optical element in each corner. More information about light guides may be found in patent applications US2017/0126868 A1 and US2017/0124377 A1, titled “System and method for reducing the number of ports associated with a mobile device.”

With continued reference to the example shown in FIG. 9, a tweeter **905** (a loudspeaker designed to reproduce high frequencies) is disposed beneath the display panel **401**, such that the tweeter **905** is close to a narrow gap **904** at the upper border of the smartphone **100**. Furthermore, a woofer or midrange speaker **906** (a loudspeaker designed to reproduce lower frequencies) is disposed beneath the display panel **401**, such that the woofer or midrange speaker **906** is near the tweeter **905**. An audio crossover or frequency crossover may be used to connect the tweeter **905** and the woofer **906**

(or midrange speaker) to the I/O interface **204**, as per FIG. 2. The audio crossover may split up an audio signal into two (or more) frequency ranges, so that the signals can be sent to loudspeakers that are designed for these frequency ranges.

Compared to the earpiece **103** as per FIG. 3, the narrow gap **904** as per FIG. 9 may be even smaller, because only high frequencies must pass through this opening. For example, a few small holes (instead of a gap) may be sufficient. No opening may be required for the lower frequencies produced by the woofer **906** (or midrange speaker).

Optionally, a second pair of tweeters **905** and woofers **906** (or midrange speakers) may be disposed close to a second narrow gap **904** at the lower border of the smartphone **100**. This may allow for playing audio in stereo if the user holds the smartphone **100** horizontally, e.g., while playing a movie in landscape mode.

FIG. 10 shows the front side of a fifth embodiment characterized by a “point symmetrical” arrangement, that is, in this example, a front-facing camera (lens **102**) is located both in the upper left-hand corner and lower right-hand corner of the display screen **101**. Furthermore, an optical infrared emitter **1001** (e.g., IR-LED) is located both in the upper right-hand corner and the lower left-hand corner of the display screen **101**. The optical infrared emitter **1001** (IR-LED) may illuminate the user’s face, e.g., in low light conditions, to support face recognition, face tracking, or eye tracking by means of the front-facing camera (lens **102**). For example, the optical infrared emitter **1001** may project dots, patterns, or spots on the face of the user to facilitate determining the shape of the users face.

Due to the symmetry, the user can rotate the smartphone **100** by 180 degrees, and a front-facing camera is still available in the upper left-hand corner. (The upper part of the smartphone **100** typically is the preferred location for the front-facing camera, e.g., when taking a “selfie” or for video telephony.) An orientation sensor or accelerometer, connected to the I/O interface **204** (as per FIG. 2), may measure the direction of gravity. By determining the current orientation of the smartphone **100**, the computer system **200** may activate the presently upper front-facing camera for capturing images. Accordingly, depending on the orientation, the screen content may be rotated by 180 degrees, e.g., as soon as the user rotates the “symmetric” smartphone **100** by approximately 180 degrees.

FIG. 11 shows the rear side of the “symmetric” smartphone **100** as per FIG. 10. Two rear-facing cameras (lens **1101**) may be located near the upper and lower edges of the rear side of the smartphone **100**. The upper camera may be the active camera, or both cameras may be used to take stereoscopic 3D images in landscape mode. Alternatively, a single rear-facing camera may be located at the center, as indicated by the lens **1102** (shown in dotted lines).

FIG. 12 shows a top plan view, FIG. 13 shows a bottom plan view, and FIG. 14 shows a side view of the “symmetric” smartphone **100** in accordance with the fifth embodiment. Furthermore, instead of a flat display screen **101**, as shown in FIG. 7 by way of example, all embodiments disclosed in this specification may be designed with a slightly curved display screen **101**, as shown in FIG. 14.

FIG. 15 is a top plan view of a sixth embodiment. A front-facing camera (lens **102**) is located in the upper left-hand corner, a proximity/light sensor **104** is located in the upper right-hand corner, an LED indicator **105** is located in the lower left-hand corner, and a fingerprint sensor **903** is located in the lower right-hand corner of display screen **101**. The LED indicator **105** may indicate the operating states

“on,” “off,” and “battery is charging,” i.e., the accumulator of the smartphone **100** is charging.

The occupied space of these sensors and/or emitters at the corners of the display screen **101** may additionally be used as touch keys. As soon as a touch key is tapped, a defined function may be triggered.

In the sixth embodiment, the touch keys at the corners of the display screen **101** are used for navigation functions of a user interface, thereby gaining additional space on the display screen **101** for other applications (“apps”). The user interface may be part of an operating system running on the computer system **200** of the smartphone **100**.

For example, in the prior art, a conventional smartphone typically displays a navigation bar with soft keys (e.g., “Home,” “Back,” “Recent apps”) at the bottom of the touchscreen display, similar to the screen content shown in FIG. 10. With regard to the sixth embodiment shown in FIG. 15, the space needed for the navigation bar now is available for other purposes (such as the speech bubbles of a chat or messenger app).

The touch keys, as per FIG. 15, located in front of the sensors and/or emitters **104**, **105**, **903**, may operate using the touchscreen functionality of the regular display screen **101**. For example, as soon as a touch or tap gesture is detected at a corner of the touchscreen—on the location of a sensor or emitter **104**, **105**, **903**—this is interpreted as an input for the dedicated touch keys “Home,” “Back,” or “Recent apps.” For this purpose, a transparent touchscreen panel that extends to the entire front side of the smartphone **100** may be disposed between the cover glass **405** and the display panel **401**.

Alternatively, in other embodiments, each touch key (located in front of the optical sensors and/or emitters **104**, **105**, **903**) may have its own dedicated touch sensor. The dedicated touch sensors may be connected to the I/O interface **204** (as per FIG. 2) and may be realized as transparent capacitive touch sensors, as transparent resistive touch sensors, or may work by means of optical imaging. In the case of optical imaging, the existing optical sensors (e.g., front camera **102**, light sensor **104**, fingerprint sensor **903**) may be repurposed as touch sensors for the touch keys; for example, in accordance with FIG. 15, the proximity/light sensor **104**, which can also measure the distance to a finger, can be repurposed as a touch sensor for the “Recent apps” touch key.

Printed symbols **1501**, **1502**, **1503** for the navigation functions of the user interface or operating system may surround the optical sensors and emitters **104**, **105**, **903**, as shown in FIG. 15: printed symbol **1501** (schematic house) for “Home key,” i.e., exit application and go back to home screen; printed symbol **1502** (schematic arrow) for “Back key,” i.e., go back to the previous screen; printed symbol **1503** (square) for “Recent apps key,” i.e., recently used applications and favorites. The printed symbols **1501**, **1502**, **1503** may surround the optical sensors and/or emitters **104**, **105**, **903** entirely, as shown in FIG. 15, or only partially. For example, instead of the schematic arrow **1502**, which surrounds the LED indicator **105** entirely, a U-turn arrow may be printed that surrounds the LED indicator **105** only in part.

The printed symbols **1501**, **1502**, **1503** may be printed (e.g., in white color) on the front surface of the cover glass **405** or preferably back-to-front on the inside of the cover glass **405**. Alternatively, the printed symbols **1501**, **1502**, **1503** may be printed on a transparent layer that is disposed beneath the cover glass **405** and located in front of the sensors and/or emitters **104**, **105**, **903**; e.g., a transparent touchscreen panel or a dedicated layer such as a plastic film.

11

Furthermore, the printed symbols **1501**, **1502**, **1503** should have a suitable shape and position, such that the light path of the optical sensors and/or emitters **102**, **104**, **105**, **903** is not blocked. For instance, a gear icon consisting of the outer shape of the gear may represent a setup screen or setup function of the operating system. Furthermore, the printed symbols **1501**, **1502**, **1503** should not hide any part of the active screen area of the display panel **401**. It is to be expressly noted that the printed symbols **1501**, **1502**, **1503** are not displayed by the display panel **401** to maximize the available space on the display screen **101** for other screen content.

FIG. **16** is a perspective view of a seventh embodiment of the smartphone **100**. A front-facing camera (lens **102**) is located in the upper right-hand corner, and a light guide **901** that combines several optical sensors and emitters (e.g., proximity/light sensor) is located in the upper left-hand corner. FIG. **17** shows a sectional view of the smartphone **100** taken at the sectioning plane and in the direction indicated by section lines **17-17** (in FIG. **16**). As can be seen in the drawings, the display screen **1601**, or rather the display panel **1702**, has a curved edge on the left, a curved edge **1602** on the right, and a curved edge **1603** at the top.

The display panel **1702** may be a flexible display, which enables the display panel **1702** to be bent, rolled, or curved at the edges. For example, a flexible OLED-based display may comprise a flexible substrate on which the electroluminescent organic semiconductor is deposited.

It can cause problems to bend a flat display panel at more edges than the left and right edges. Bending a flat display panel at the top edge—in addition to the left and right edges—may crumple, crease, or kink the display panel at the corners or may cause problems with the lamination process.

Regarding the seventh embodiment, to avoid that the display panel **1702** gets crumpled, creased, or kinked at the corners, the upper left and right corners of the display panel **1702** have a cutout **601** substantially in a convex shape, e.g., a rectangular shape, an oval shape, a curved shape, or a quarter circle; see convex cutout **601** in FIG. **6**. This effectively prevents the problems described above: the cutouts **601** at the upper corners allow the display panel **1702** to be bent at two orthogonal edges **1602**, **1603** at the same time. The lens **102** and the light guide **901** are disposed at the locations of the cutouts **601**, and thus the cutouts **601** serve two purposes at the same time.

Referring to FIG. **17**, which shows the sectioning plane **17-17**, a flexible display panel **1702** (e.g., a flexible OLED-based display) is disposed beneath a cover glass **1701**. As can be seen in the sectional view, the cover glass **1701** has a curved edge **1603** at the top, and the display panel **1702** is bent to the rear at the upper edge. In FIG. **17**, the remaining casing of smartphone **100** (e.g., lower part, bottom side) is indicated as a dotted line.

Bending a flexible display panel **1702** to the rear of the display panel **1702** at the left, right, and upper edge makes it possible to reduce the outer horizontal and vertical measurement of the smartphone **100** while keeping the original (utilizable) surface area of the display panel **1702**. In other words, the smartphone **100**, as per FIG. **16** and FIG. **17**, features a maximized screen surface and minimized outer dimensions. In some embodiments, the flexible display panel **1702** may have cutouts **601** at all four corners, and the lower edge of the display panel **1702** is bent to the rear—similar to the upper edge.

Optionally, as shown in FIG. **17**, a piezoelectric speaker **1703** (e.g., piezo film speaker with piezo actuator) may be

12

disposed beneath the display panel **1702**. The piezoelectric speaker **1703** may serve as an earpiece for telephone calls.

FIG. **18** is a perspective view of an eighth embodiment. The eighth embodiment corresponds to the seventh embodiment (as per FIG. **16** and FIG. **17**), except that, instead of the piezoelectric speaker **1703**, two ear speakers **1802**, **1803** are disposed beneath (or close to) the cutouts **601** in the upper left and right corners, i.e., near the light guide **901** and the lens **102** of the front-facing camera. As shown in the drawing, the earpiece for each ear speaker **1802**, **1803** (on the left and right) may consist of a plurality of small holes or openings **1801** that partially surround the light guide **901** on the left and the lens **102** on the right, wherein the small holes or openings **1801** are still located in the areas of the two convex cutouts **601** of the display panel **1702**, so that the sound waves are not blocked by the adjacent display panel **1702**.

This approach maximizes the remaining area of the display screen **1601** while providing the necessary openings for the ear speakers **1802**, **1803**. The small holes or openings **1801** may have any suitable arrangement or shape. For example, the small holes or openings **1801** may be arranged in a quarter circle. Furthermore, instead of a plurality of small holes **1801**, each opening (on the left and on the right) may consist of a single curvilinear slot or slit.

In effect, the smartphone **100**, as per FIG. **18**, features two earpieces for telephone calls: one earpiece **1801** in the upper-left corner and one earpiece **1801** in the upper-right corner of the display screen **1601**. During a telephone call, while holding the smartphone **100** to the ear, the user may use the uppermost earpiece **1801** of the smartphone **100**. In this context, “uppermost earpiece” means the earpiece **1801** with a higher position while holding the smartphone **100** like a telephone receiver. Expressed differently, for convenience, the user may hold or press the uppermost corner of the smartphone **100** to his/her ear, while the lower corner of the smartphone **100** is at the level of the neck.

Depending on whether the user holds the smartphone **100** to the left or right ear, the smartphone corner with the light guide **901** (on the left in FIG. **18**) or the smartphone corner with the lens **102** (on the right in FIG. **18**) may be the location of the uppermost ear speaker, and since the user holds the uppermost ear speaker to his/her ear, the lower ear speaker (at the level of the neck) may be switched off.

An orientation sensor or accelerometer **1804** may be used to determine the current orientation of the smartphone **100**. The accelerometer **1804** may be connected to the I/O interface **204** (as per FIG. **2**) and may measure the direction of gravity. For example, with reference to the coordinate system **1805** shown in FIG. **18**, if the gravity primarily points in the positive direction of the X-axis, the ear speaker **1803** (close to lens **102** on the right) may be switched off. If the gravity primarily points in the negative direction of the X-axis, the ear speaker **1802** (close to light guide **901** on the left) may be switched off. Optionally, in other embodiments, both ear speakers **1802**, **1803** (on the left and right) may operate simultaneously and may possibly focus the sound on the ear.

The approach described above with respect to the eighth embodiment, is not limited to smartphones **100** with curved edges. Likewise, a smartphone **100** with a flat display screen **101**, such as the smartphone **100** shown in FIG. **7**, may feature two ear speakers disposed at the location or near the location of the cutouts **601**, wherein the presently lower ear speaker may be switched off, or wherein both ear speakers are outputting the sound of the telephone call.

13

FIG. 19 shows the front side of a ninth embodiment, namely a smartwatch 1900 as a further example of a mobile electronic device. The smartwatch 1900 and the display screen 101 can have any suitable aspect ratio. In this example, the display screen 101 (or rather the display panel 401) has a convex cutout 601 in the upper right-hand corner and a convex cutout 601 in the lower left-hand corner. Accordingly, a lens 102 of a front-facing camera is located in the upper right-hand corner, and an LED flashlight 1901 is located in the lower left-hand corner. Alternatively, the two cutouts 601 and the sensors/emitters 102, 1901 may be located in the upper left-hand corner and lower right-hand corner, or any other combination of corners. The LED flashlight 1901 may serve as a flashlight for taking photos or as an emergency flashlight, pocket torch, or pocket lamp. The front-facing camera (lens 102) may be used to take a "selfie." In the example, as per FIG. 19, the display screen 101 displays a picture or photograph that seamlessly extends over the entire width and over the entire height of the display screen 101.

Optionally, with continued reference to FIG. 19, the two convex cutouts 601 (for the lens 102 and the LED flashlight 1901) additionally may serve as touch keys for functions of the smartwatch 1900, as described above with regard to the sixth embodiment (FIG. 15).

The embodiments shown in FIG. 3 through FIG. 19 maximize the effective area of the display screen 101, 1601 or display panel 401, 1702 in relation to the outer dimensions of the mobile electronic device 100, 1900. However, if a conventional user interface or a conventional application (app) that is running on the computer system 200 displays screen content in "full screen" using the entire height and/or width of the display panel 401, parts of the screen content may be missing at the corners due to the cutouts 601. To avoid this, embodiments of the present invention may use the flowcharts shown in FIG. 20, FIG. 21, and FIG. 22. The flowcharts may be implemented as a hardware circuit or as software running on the computer system 200. A hardware implementation may be realized as a field programmable gate array (FPGA) or as an application specific integrated circuit (ASIC). A software solution may run on the processor 201 and/or the graphics sub-system 108, as per FIG. 2; e.g., a CPU with an integrated graphics processing unit (GPU).

The screen content rendered by the graphics sub-system 108 and displayed on the display screen 101, 1601 by means of the display panel 401, 1702 may consist of screen objects or graphic objects, referred to herein as "objects." A coordinate system (X, Y) may be used to position the objects on the display screen 101, 1601 and/or to scale the size of the objects. Objects used by an application and/or operating system, running on the computer system 200, may comprise, inter alia, picture elements, icons, buttons, text lines, bars, and boxes, etc.

The flowchart 2000, shown in FIG. 20, may be used to handle certain parts of screen objects or graphic objects that would be missing on the display screen 101, 1601 due to the cutouts 601. This may be done before the objects are rendered by the graphics sub-system 108. In step 2001 of the flowchart 2000, it is checked whether the object in question is affected by a cutout 601. For example, by comparing the X and Y coordinates of the outer shape of the object with the corresponding X and Y coordinates of the outer shape of the cutout 601, it can be determined whether the object and the cutout 601 are overlapping or "colliding." If the object and the cutout 601 are not overlapping, the object can be

14

rendered without any changes by graphics sub-system 108 (i.e., position and size as originally intended). This is done in step 2002.

Otherwise, if the object and the cutout 601 are overlapping, the object type or category is determined in step 2003. The objects used by the user interface and/or by applications may be categorized depending on their properties, such as purpose, size, relevance, etc. For example, there may be a category of essential elements that are required for user interaction, such as icons, buttons, text lines, checkboxes, drop-down boxes, sliders, and other control elements. Furthermore, there may be, for instance, a category of less essential elements, such as frames, bars, pictures, and the outer lines of dialog boxes and balloons.

Optionally, a configuration menu or setup option may allow the user to configure the relevance or importance level of object types or categories as a personal preference. In this way, the user can decide for himself/herself which screen objects (pictures, text, etc.) are considered to be essential or important. This option applies to all subsequent cases.

In step 2004, it is checked whether the object in question belongs to the type of ornamental or portioning elements (e.g., frames, bars, background color, the outer lines of dialog boxes or balloons). If this is the case, the object is rendered without any changes in step 2005 by the graphics sub-system 108 (using the original position and size), because it is assumed that the screen content is still intelligible even if, by way of example, the outer line of a frame or dialog box is interrupted by a cutout 601.

In step 2006, it is checked whether the object in question is flowing text (continuous text comprising several lines and wordwraps). If applicable, the flowing text is reformatted depending on the embodiment of the display panel 401, i.e., depending on the location of the cutout(s) 601. This is done in step 2007. If the display panel 401 has a cutout 601 in the upper-left corner, reformatting is done by indenting the uppermost line(s), and if a cutout 601 is located in the lower-left corner, reformatting is done by indenting the lowermost line(s), such that the flowing text and the cutout(s) 601 no longer overlap. If the display panel 401 has a cutout 601 in the upper or lower right-hand corner, reformatting is done by moving the position of the word wrap to the left, so that the last word(s) of the affected uppermost or lowermost line(s) no longer overlap with the cutout(s) 601; i.e., after reformatting, the affected line(s) are shorter. The number of lines that are shortened depends on the font size and the height of the cutout(s) 601.

In step 2008, it is checked whether the object in question is a full screen video, a computer game, or full screen 3D graphics, referred to herein as full screen objects. Full screen objects may extend seamlessly over the entire height and/or width of the display screen 101. If applicable, full screen objects are handled by the separate flowchart 2100 shown in FIG. 21 and described below (subroutine call in step 2009).

Next, since the object in question is not a "special case" (like the portioning elements, full screen objects, or flowing text), it is checked in step 2010 whether it is possible to move the position of the object. This may depend on neighboring objects and the gaps between the elements. See FIG. 22 through FIG. 25 and the corresponding description below. If it is possible to move the object, the object (and possibly adjacent objects) is moved away from the cutout(s) 601 in step 2011, such that the object and the cutout(s) 601 no longer overlap. Typically, this involves shifting the object (and possibly adjacent objects) horizontally, vertically, or slightly to the center of the display screen 101.

15

If it is not possible to move the position of the object for some reason (e.g., neighboring objects cannot be moved either), special actions must be performed depending on the object type. This is done in the subsequent steps, starting with step **2012**.

If the object in question is a single text line, such as a title, caption, or headline, and since it is not possible to move this text line, the font size or the character width of the text line is reduced in step **2013** such that the text line and the cutout(s) **601** no longer overlap.

Referring to step **2014**, if the object in question is an essential element that is required for user interaction (e.g., an icon, button, checkbox, drop-down box, slider, or other control element) it may not be appropriate to reduce the size of this object significantly, because this may hinder usability. Instead, the size of other less important or less relevant objects may be reduced. Essential objects are handled by the separate flowchart **2200** shown in FIG. **22** and described below (subroutine call in step **2015**).

In other embodiments, the entire screen content may be resized to a smaller size in step **2015**, so that the essential element and the cutout(s) **601** no longer overlap and, in exchange, a margin (e.g., in black) is added to the left, right, top, and/or bottom area of the display screen **101**, depending on the location of the cutout(s) **601**. As a result, the essential element is reduced far less in size because all other objects on the screen are reduced slightly in size as well. Optionally, the width and height may be scaled independently.

In step **2016**, it is checked whether the object in question is a picture element. The picture element may be a bitmap image stored in a known file format such as BMP, JPG, GIF, or PNG. If the object is a picture element, a text recognition may be performed in step **2017**, that is, the bitmap content of the picture element may be analyzed by means of optical character recognition (OCR). Any known techniques may be used for the OCR process, including (but not limited to) line and word detection, character isolation or segmentation, character recognition using matrix matching, and/or feature extraction.

Next, in step **2018**, if the OCR process does not detect any (or any relevant) text, words, numbers, characters, logo designs, or other symbols that overlap with the cutout(s) **601** at the corner(s) of the display screen **101**, the picture element can be rendered by the graphics sub-system **108** without any changes (position and size as originally intended; step **2019** in the flowchart), because it is assumed that picture sections without characters or symbols are less important to the user. Other embodiments may be implemented without an OCR process, i.e., all pictures are rendered without changes (step **2019**, wherein steps **2017** and **2018** are skipped), and it is simply assumed that pictures or photographs usually do not contain essential information near the picture border. It is to be expressly noted that the picture element may contain text or characters in the middle of the picture or at other locations that are not overlapping with the cutout(s) **601**. In such a case (e.g., a symbol or text near the center of the picture), the position and size of the picture element can remain unchanged.

Otherwise, if relevant symbols or characters (e.g., the beginning of a word) are found at the location of a cutout **601**, the picture element may be scaled to a smaller size in step **2020**. Thanks to the smaller size, the picture element may now be moved away from the cutout **601** (to some extent), so that relevant symbols or characters in the picture are viewable.

Alternatively, instead of scaling the picture element to a smaller size, the relevant, but (partially) invisible symbol(s)

16

or text message found at a corner of the image, may be copied to an other location within the image (i.e., less close to the corner). This can be done by means of image processing and/or picture manipulation; for example, by means of copy operations applied to the bitmap image. The new location for the symbol(s) or text message preferably is chosen in such a way that no important picture areas are hidden or affected by the moved symbol(s) or text message. The symbol(s) or text message may be moved as a block, including the background, or may be extracted from the picture background, e.g., by means of object recognition and/or OCR, so that the picture background at the new location remains partially visible.

Finally, in step **2021** of flowchart **2000**, if the object in question does not belong to any of the categories listed above, the (unknown) object may be scaled to a smaller size and may be moved slightly, such that the object and the cutout(s) **601** no longer overlap.

In other embodiments, support for additional object types may be implemented. For example, support for vector graphics and/or graphical primitives (e.g., ellipse, circle, rectangle, or polygon) may be added. The lines and/or branching points of the vector graphics or graphical primitives may be categorized by relevance, and the vector graphics or graphical primitives may be scaled accordingly so that only less important parts (e.g., a continuous polyline) are interrupted by the cutout(s) **601**.

If the display panel **401**, **1702** has more than one cutout **601**, for instance, cutouts **601** in the upper left- and right-hand corners, the procedure described in the flowchart **2000** (as per FIG. **20**) may be executed for each cutout **601**.

Flowchart **2100**, shown in FIG. **21**, may be used to handle full screen objects such as full screen videos, computer games, and full screen 3D graphics. Full screen objects may seamlessly extend over the entire height and/or width of the display screen **101**. For example, a display panel **401** may have a cutout **601** at the upper-left corner and a cutout **601** at the upper-right corner; a full screen object like a computer game may be displayed in portrait orientation and may extend seamlessly over the entire vertical screen height of the display panel **401** from the upper edge to the lower edge of the display panel **401** such that the uppermost part of the full screen object (e.g., the computer game) is displayed between the upper-left cutout **601** and the upper-right cutout **601**. In an other example, a 3D graphics scene is displayed in landscape orientation, wherein the 3D graphics scene may extend seamlessly over the entire horizontal screen width of the display panel **401** from the left edge to the right edge of the display panel **401**.

Referring to FIG. **21**, in step **2101** of the flowchart **2100**, the object type or category of the full screen object may be determined. Full screen objects may be categorized, e.g., by purpose or relevance.

In step **2102**, it is checked whether the object type is "3D graphics," for example, a computer game. Typically, the graphics of a computer game, generated by a 3D engine, consists of two parts: the 3D graphics scene (with objects such as landscapes, buildings, vehicles, humans, and animals) and an overlay layer (with overlaid objects such as a score, speedometer, status message, or text overlay). With regard to step **2103**, overlaid objects may be moved separately and may be managed using the flowchart **2000**, as per FIG. **20**. (See "single text line" and "picture element" in step **2012**, step **2013**, and steps **2016** through **2020**.) The 3D graphics scene may be rendered by the graphics sub-system **108** without changes using the entire width and/or height of the display screen **101**. Note that in this non-limiting

17

example, it is assumed that overlaid objects (like a score) should be readable, while the 3D graphics scene is still usable even if some areas are missing at the corners of the display screen **101** due to the cutouts **601**.

In step **2104**, it is checked whether the object type is “full screen video,” for example, a live-stream or the playback of a video file. The video file may be stored in a known format, such as MP4 or AVI. In this non-limiting example, the full screen video is displayed in “landscape mode,” that is, the user holds the smartphone **100** horizontally.

If the present object is a full screen video, the aspect ratio of the full screen video is checked in step **2105**. Next, in step **2106**, if the aspect ratio of the full screen video and the aspect ratio of display panel **401**, **1702** are approximately equal, the output of the video may be scaled to a slightly smaller size, so that the corners of the video are somewhat more visible. This is referred to as “windowboxing.” For example, if both the full screen video and the display panel **401**, **1702** have an aspect ratio of 16:9, the video may be slightly reduced in size while maintaining the original aspect ratio of the video. As a result, smaller regions of the corners of the video are missing due to the cutouts **601**. (Optionally, the user may be able to activate or deactivate this behavior as a preference.)

In step **2107**, it is checked whether the full screen video has an aspect ratio that is wider, i.e., greater, than the aspect ratio of the display panel **401**, **1702** (“wide-screen aspect ratio”). For example, this would be answered in the affirmative if the full screen video is a feature film in the Panavision® or CinemaScope® format 2.35:1, while the display panel **401**, **1702** has an aspect ratio of 1.78:1, better known as 16:9.

In step **2108**, if the aspect ratio of the full screen video is greater than the aspect ratio of the display panel **401**, **1702**, the full screen video is displayed in a new variant of the “letterboxing”-mode: Horizontal matte regions, typically black bars, are added at the top and/or at the bottom of the full screen video (which is displayed in landscape mode using the entire width of the display panel **401**, **1702**) such that the cutouts **601** of the display panel **401**, **1702** are accommodated, at least in part, in the horizontal matte regions. As a result, no parts (or at least fewer parts) of the full screen video are invisible due to the cutouts **601**.

Otherwise, in step **2109**, if the aspect ratio of the full screen video is smaller than the aspect ratio of the display panel **401**, **1702**, the full screen video is displayed in a mode referred to as “pillarboxing.” For example, the full screen video may have a classic aspect ratio of 4:3, and the display panel **401**, **1702** may have an aspect ratio of 16:9. In another example, the full screen video has a 16:9 aspect ratio, and the display panel **401**, **1702** has an aspect ratio of 21:9. In these cases, vertical bars (e.g., in black) are added at the left and/or right side of the full screen video (displayed in landscape mode) such that the cutouts **601** of the display panel **401**, **1702** are located in the region of the vertical bars. As a result, no parts (or at least fewer parts) of the full screen video are invisible due to the cutouts **601**.

Finally, in step **2110**, if the full screen object in question does not belong to the categories discussed above, the (unknown) full screen object may be scaled to a smaller size and, if applicable, may be moved slightly, such that the full screen object and the cutouts **601** no longer overlap. In other embodiments, support for additional object types may be implemented.

In step **2011** of FIG. **20**, it is mentioned that the possibility of moving an object may depend on neighboring objects that may block the necessary shift of the object. The flowchart

18

2200, shown in FIG. **22**, handles such situations. (If no consideration of neighboring objects would be taken, the shifted object and neighboring objects would overlap.)

In step **2201** of the flowchart **2200**, as per FIG. **22**, it is checked whether adjacent object(s) get in the way when repositioning the current object away from a cutout **601**. If no objects are blocking the shift, the current object is moved in step **2202**, such that no parts of the object are overlapping with the cutout **601**. The object may be moved horizontally, vertically, diagonally, or in any other suitable direction.

Otherwise, in the case that adjacent object(s) are blocking the shift of the current object, it is checked in step **2203** whether the adjacent object(s) can be moved. If applicable, the adjacent object(s) are moved where necessary so that the current object can be moved as well (away from the cutout **601**). This is done in step **2204**. Since the adjacent object(s), in turn, may be blocked by other neighboring objects, a recursive algorithm may be used for this purpose. Depending on the arrangement, it may not be necessary to move all adjacent objects.

If it is not possible to make the necessary changes in position, that is, if at least one adjacent object cannot be moved for any reason, it is checked in step **2205** whether the current object is more important than the inflexible adjacent object(s). For this purpose, the objects may be categorized by relevance, purpose, size, etc. For example, there may be essential objects with high relevance (e.g., a button, checkbox, drop-down box, or slider) and ornamental objects with low relevance (e.g., a frame or a picture). Categorizing by relevance and/or purpose may involve distinguishing between interactive elements and static elements, and eventually, it may be less problematic to reduce the size of a large object.

If the current object (e.g., a button) is more important than each inflexible adjacent object (e.g., pictures), then the adjacent object(s) are scaled to a smaller size in step **2206**, and the gained space is used to move the current object away from the cutout **601** to make it fully visible. Otherwise, if the current object is less important than the adjacent object(s), the size of the current object is reduced in step **2207**, so that (thanks to the smaller size) the current object can be moved away from the cutout **601**, at least slightly.

Optionally, a list with all participating and/or affected objects on the screen may be sorted by relevance. In this way, the least important objects are known. The least important objects may be preferred candidates for a reduction in size.

FIG. **23** shows, by way of example, graphic objects of a conventional application (app) that is not optimized for the four cutouts **601** at the corners of the display screen **101**. A medium-sized picture element **2301**, e.g., a logo, symbol, or other design, is located in the upper left-hand corner of the display screen **101**. In this example, the upper part of the letter “L” is invisible due to the cutout **601**. Four small icons **2302** through **2305** are located on the right, next to the picture element **2301**. In this example, the icons are essential elements of the user interface and must be visible. Yet, the last icon **2305** is partly invisible due to the cutout **601** in the upper right-hand corner, which makes the icon **2305** practically unrecognizable and/or inoperable. The screen content in the lower area of the display screen **101** consists of a large picture element **2306** with a photograph, e.g., a JPG image file. The text in the lower right-hand corner of the picture element **2306** is part of the bitmap data of the image (and not a separate text string). As can be seen, the name after “Photo taken by . . .” has been truncated by the cutout **601** (and hence is unrecognizable).

The operating system, on which the conventional app is running, may adjust the size and position of the graphic objects using the approach outlined in flowchart **2000** (FIG. **20**) and flowchart **2200** (FIG. **22**), so that all relevant or substantial elements are visible. The solution shown in FIG. **24** is based on the directive to move objects horizontally.

An analysis of the relevance of icon **2305** (step **2003** in flowchart **2000**) indicates that icon **2305** is essential and must be moved to the left horizontally. This shift is blocked by the adjacent icons **2302**, **2303**, **2304**, which are also essential and too small to reduce their size, so that, by means of flowchart **2200**, it is determined that all four icons must be moved to the left (e.g., recursive algorithm). The medium-sized picture element **2301** has a lower level of importance and is large enough so that a reduction in size is acceptable. See step **2203** and step **2205** in flowchart **2200**.

Optionally, optical character recognition (OCR) may be applied on the medium-sized picture element **2301**. The analysis may show that the letters in “LOGO” are big and that it is acceptable that a part of the letter “L” remains invisible. Hence, the picture element **2301** is reduced in size, but only shifted slightly to the right.

With continued reference to FIG. **24**, optical character recognition (OCR) at the corners of the large picture element **2306** (photo) will discover the small text at the lower right-hand corner; see step **2017** in flowchart **2000**. As a result, and in accordance with step **2020**, the picture element **2306** is scaled to a smaller size and is moved horizontally to the left, such that the name “Alice” becomes visible. Since no relevant symbols or characters have been found (by OCR) in the lower left-hand corner of the picture element **2306**, it is acceptable that this corner of the photo is cut off by the cutout **601**. Alternatively, as shown in FIG. **25**, a directive to move the objects diagonally toward the center of the display screen **101** may be applied as indicated by means of the arrows **2501**.

Optionally, advanced methods, such as a trained neural network, may be used to improve rearranging the graphic objects on the screen. Neural networks may be trained to distinguish important objects from less important objects, and they may be trained with a set of preferable layouts that are both visually appealing and user-friendly while avoiding the cutouts **601** as needed. The system may recognize recurring applications (“apps”) and may remember the best layout for these “apps.” Moreover, neural networks may learn from the user behavior: for example, if the user deactivates the current layout (generated by a neural network), the layout may be unfavorable.

FIG. **26** through FIG. **30** show, as an example, an HTML web page or a page of an e-book displayed on the display screen **101**. Depending on the embodiment, a web browser or a dedicated reader app, running on the smartphone **100**, may be used for rendering the content of the HTML web page or e-book. In the example as per FIG. **26**, the flowing text **2601** is not optimized for the four cutouts **601** at the corners of the display screen **101**. As a result, a few words of the story (“Alice’s Adventures in Wonderland,” in the public domain) are truncated or missing at the corners. For example, the word “by” is completely invisible due to the cutout **601** in the upper right-hand corner.

Referring to FIG. **27**, an embodiment is shown that indents the flowing text **2601** at the cutouts **601** on the left and that changes the position of the word wrap on the right, so that no part of the text is invisible due to the cutouts **601**; see step **2007** in flowchart **2000**. Optionally, as shown in FIG. **27**, the size of the indent and the position of the word

wrap may vary from line to line to tailor the length of the lines to the convex shape of the cutouts **601**.

As can be seen by comparing FIG. **27** with FIG. **26**, the word wraps of the entire first paragraph of the story have changed; e.g., there is a new seventh line that reads: “conversations?” If the text of the story were to be scrolled down, e.g., in a web browser, the word wraps of (at least) the uppermost paragraph would change permanently while scrolling, which may elicit a poor user experience. Therefore, the embodiment as per FIG. **27** may be preferable if the pages are not scrollable; e.g., the user may turn the pages of an e-book by means of a swipe gesture (to the left or right) on the touchscreen.

The embodiment as per FIG. **28** and FIG. **29** is designed to scroll a text block **2801** up and down without the aforementioned problem of permanently changing word wraps (e.g., in the uppermost paragraph on the screen). This is achieved by dynamically changing the character width (also known as type width or font width) and/or the character spacing (also known as walking distance or tracking) while keeping the original height of the characters and the original line spacing.

Referring to FIG. **28**, the character width of the first two lines and last two lines has been reduced such that all words of the original lines (as they would appear in FIG. **26** without the cutouts **601**) fit into the reduced width between the cutouts **601**; e.g., the words “sitting by” are still displayed in the first line and not in the second line (as per FIG. **27**). At the top and/or bottom of the display screen **101**, the character width and/or character spacing may vary from line to line to tailor the length of the lines to the convex shape of the cutouts **601**. Since the vertical position of the lines changes permanently while the user scrolls the page, the character width and/or character spacing may be adjusted continually for those lines that are in the region of the cutouts **601**—until the user stops scrolling.

FIG. **29** shows the same text block **2801** scrolled down by one line. While the first line of the story now is invisible, the character width of the second and third lines has been reduced as they become the upper lines (displayed on the display screen **101**). As can be seen by comparing FIG. **29** with FIG. **28**, the word wraps (e.g., of the first paragraph of the story) have not changed, resulting in a good user experience while scrolling. Therefore, the embodiment as per FIG. **28** and FIG. **29** may be preferable for scrollable text, such as an HTML web page displayed in a web browser.

FIG. **30** and FIG. **31** show a further example: The display panel **401** of the smartphone **100** has an upper-left cutout **601** and an upper-right cutout **601** at the upper corners. The computer system **200** of the smartphone **100** may be configured or programmed to display scrollable screen content on the display panel **401**, e.g., an HTML web page rendered by a web browser, a scrollable document, a scrollable e-book, or scrollable content of an app that is running on the computer system **200**. The scrollable screen content seamlessly extends over the entire height of the display panel **401**, such that the uppermost part of the screen content is displayed between the upper-left cutout **601** and the upper-right cutout **601**.

Based on an user input, the computer system **200** may determine that the screen content is to be scrolled vertically, e.g., the user may perform a (vertical) swipe gesture on the touchscreen **101**. Next, based on the current vertical scrolling position of the screen content, the computer system **200** may identify one or more screen objects that overlap with the area of the upper-left cutout **601** or the upper-right cutout

21

601 and may determine the object categories of these screen object(s) as per flowchart 2000 (FIG. 20). The object categories may comprise at least text lines and pictures. The picture 2306, shown in FIG. 30, may be a drawing or a photograph and may belong to the “pictures” category, and the lines of the text block(s) 2801 may belong to the “text lines” category.

While scrolling, the graphics sub-system 108 may render updated screen content repeatedly (e.g., with a defined frame rate), at least as long as the scrolling lasts. Each text line of the text block(s) 2801 that overlaps with the area of the upper-left or upper-right cutout 601 may be modified by reducing the character width and/or character spacing while keeping the original height of the characters and the original line spacing. The length of each text line may be tailored to a predetermined shape derived, at least in part, from the shape of the upper-left or upper-right cutout 601. This is shown in FIG. 30 by means of the three uppermost lines of the upper text block 2801. Since the vertical position of the lines changes permanently while the user scrolls the screen content, the character width and/or character spacing may be adjusted continually for those lines that are in the region of the cutouts 601—until the user stops scrolling.

Screen objects belonging to the “pictures” category, such as the picture 2306 in FIG. 30, may be rendered by the graphics sub-system 108 without changes to the size, i.e., using the original or intended size, because it is assumed that a picture still is clear even if a region near the border of the picture is invisible due to the upper-left or upper-right cutout 601. This situation is shown in FIG. 31, which shows the screen content of FIG. 30 scrolled down by approximately six lines.

The embodiments disclosed in FIG. 20 through FIG. 31 handle the missing screen areas at the corners of the display panel 401, 1702 by scaling and/or shifting graphic objects selectively; for instance, by reducing the width of characters in a specific text line. However, instead of working on an object level (i.e., graphic objects), the entire screen content may be modified on a per-pixel basis, as set forth in the following embodiments.

In one embodiment, all horizontal lines of pixels on the height of the cutouts 601 (i.e., all lines of pixels located at the top and/or bottom of the display screen 101) are scaled down individually to a shorter width, such that the width of each line of pixels is tailored to the convex shape of the cutouts 601. The result is screen content with distortions near each cutout 601, yet the entire screen content is visible—no parts are missing. For example, with reference to the partially comparable effect shown in FIG. 29, there would be significant distortions near the cutout 601 in the upper left-hand corner, almost no distortions in the middle, and significant distortions near the cutout 601 in the upper right-hand corner. The extent of the distortions can be reduced by smoothing the transition and by leaving a small part of the screen unused (below the upper cutouts 601 and/or above the lower cutouts 601). The approach to leaving a small part below and/or above the cutouts 601 unused, i.e., to use a predetermined shape that is slightly different from the shape of the cutouts 601, can also be applied to the embodiments shown in FIG. 28 through FIG. 31.

In another embodiment, vertical lines of pixels (at the left and right of the display screen 101) that are affected by the cutouts 601 are scaled down to a shorter length, such that the height of each line of pixels is tailored to the convex shape

22

of the cutouts 601. Since vertical lines in this example are longer than horizontal lines, this may reduce distortions in many regions of the screen.

In yet another embodiment, especially when displaying photographs or other images, horizontal and vertical scaling may be combined. Optionally, the corners of the image may be faded to low contrast or may be blurred.

The approach outlined in flowchart 2000 (FIG. 20), flowchart 2100 (FIG. 21), and flowchart 2200 (FIG. 22) identifies essential elements, and likewise screen areas of little importance, and rearranges the screen layout accordingly. In other embodiments, users may decide for themselves whether current content that is invisible due to the cutout(s) 601 at the corner(s) is essential.

For example, if a photograph is displayed in full screen (e.g., full width and/or height) on the display screen 101, and if no essential parts of the photo are located at the corners (usually, this is the case), it is acceptable that the corners of the photo are cut off, and thus, there is no need for the user to change the current (e.g., default) display mode.

Otherwise, if the current content on the screen is, by way of example, the text of an e-book, as shown in FIG. 26, the user will notice that words are truncated or missing, e.g., at the upper corners of the display screen 101. Therefore, the user will make a defined user input that causes the operating system to move the entire screen content downward approximately by the height of the upper cutout(s) 601 (see FIG. 32). As a result, the entire upper lines of the e-book are temporarily visible. The available space between the upper cutouts 601 may be used to display a status bar 3201 with useful information and/or icons, such as signal strength, time, and battery status. The status bar 3201 may have any suitable height. For example, the status bar 3201 shown in FIG. 32 is slightly smaller than the height of the cutouts 601, and the status bar in FIG. 8 has approximately the same height as the cutouts 601. In other embodiments, the status bar 3201 may have a greater height than the height of the cutout(s) 601.

The user may switch between the “maximized view” as per FIG. 26 and the “detail view” as per FIG. 32 (and, optionally, other views or layouts) using any defined user input that is applicable. For example, a touchscreen gesture may be used, such as a “swipe-down” from the top of the display screen 101 (starting at the upper edge). In other embodiments, a novel “drag-along” or “drag-away” gesture may be used, as suggested in U.S. Pat. No. 9,323,340 B2, titled “Method for gesture control.” To switch between “maximized view” and “detail view” using the novel “drag-along” or “drag-away” gesture, the user may touch the touchscreen at any location (not necessarily at the edge) and then, while keeping his/her finger unmoved, the user shifts the smartphone 100 below the unmoved finger, such that the unmoved finger slides on the touchscreen. As soon as the gesture is detected by the operating system, and depending on the direction of the shift movement (e.g., forward or backward), the system will switch between the views.

Moreover, a variety of motion-based gestures can be used to switch between the “maximized view” and the “detail view.” For example, the user may tilt or rotate the smartphone 100 approximately around the X-axis of the coordinate system 1805 in a fast forward and backward movement causing the operating system to switch between the views.

Alternatively, pressure-sensitive sensors connected to the I/O interface 204 may be embedded within the frame of the smartphone 100, such that a squeeze to the phone’s frame can be detected. Squeezing the frame may cause a switch between the “maximized view” and the “detail view.”

23

Other embodiments may use eye tracking to switch between the views. Eye tracking may be done using the optical sensor(s) located at the cutout(s) **601**. For example, if the current view is the “maximized view,” as per FIG. **26**, and if the user looks at an upper corner (with a cutout **601**) for a defined period of time, this is recognized by the eye tracking system, and the operating system will switch to the “detail view,” as per FIG. **32**. Subsequently, if the user ceases looking at an upper corner for a prolonged span of time, the operating system may switch back to the (preferred) “maximized view.”

In some embodiments, especially if switching between the views is done via a touchscreen gesture, via motion control, or by squeezing the smartphone’s frame, the operating system automatically switches back from the “detail view” (as per FIG. **32**) to the default “maximized view” (as per FIG. **26**) after a defined period of time, because it can be assumed that it takes only a short time for the user to recognize or read the (previously truncated) text at the corner. The defined period of time can be made adjustable as a preference in the setup.

In at least one embodiment, a pop-up window or a variation of a screen magnifier may be used that displays and, if intended, magnifies the missing content truncated by the cutout **601** in another area on the display screen **101**. The pop-up window or screen magnifier may be activated by the user via a “long press” at the corner of the touchscreen. Alternatively, a pressure-sensitive touchscreen can be used that distinguishes between different levels of force being applied to the surface.

Switching between views or screen layouts is not limited to the examples discussed above. Depending on the embodiment, the number of views or layouts can be larger or smaller. For example, in a further embodiment, one or more input gesture(s) may cause switching between an adjusted layout (as per FIG. **20**, FIG. **22**, and FIG. **24**), a distorted layout (horizontal and/or vertical scaling at the pixel level), the original layout (as shown, by way of example, in FIG. **23** or FIG. **26**), and a layout with a status bar (as per FIG. **32**). Furthermore, a configuration menu or setup option may allow the user to define the preferred layout or view for each application (app) installed on the smartphone **100**. The preferred layout or view can be activated automatically as soon as a known application is started.

FIG. **33** shows an embodiment of a smartphone **100** (with a front-facing camera **102**) that maximizes the size of a wide-screen movie **3301** in relation to the outer dimensions of the smartphone **100**. The wide-screen movie **3301** may be a feature film and may have an aspect ratio of, e.g., 2.35:1, 2.39:1, 2.40:1, or 2.66:1. The wide-screen movie **3301** may be streamed over a network or wireless network or may be played locally from a video file, such as an MP4 or AVI file. In FIG. **33**, the smartphone **100** is shown in landscape orientation, and the following description is based on this orientation.

The smartphone **100** may comprise an oblong display panel **401** (aligned in landscape orientation) with an upper cutout **601** at an upper corner and a lower cutout **601** at a lower corner of the display panel **401**. Optionally, the height of the upper cutout **601** may be approximately equal to its width, as shown in FIG. **33**. Likewise, the height and the width of the lower cutout **601** may be substantially equal. In some embodiments, the upper and lower cutout **601** may have, at least in part, the shape of a quarter circle. This shape may be advantageous because it minimizes the area occupied by the upper and lower cutouts **601** while the remaining area of the display panel **401** is maximized.

24

A front camera module with a front-facing lens **102** may be disposed, at least in part, in the area of the upper cutout **601** (or, in another embodiment, in the area of the lower cutout **601**). In some embodiments, as shown in FIG. **33**, the front-facing lens **102** (of the camera) is surrounded partially by the border of the cutout **601**, substantially at a constant or minimized distance, so that the remaining area of the display panel **401** is maximized. Optionally, an optical emitter, such as an infrared (IR) LED **1001**, may be disposed, at least in part, in the area of the other cutout **601**, e.g., as shown in FIG. **33**, in the area of the lower cutout **601**.

A computer system **200** (connected to the display panel **401**, the front camera module, and the optical emitter) may be configured or programmed to display screen content on the display panel **401**, comprising a wide-screen movie **3301** in landscape orientation that seamlessly extends over the entire horizontal screen width of the display panel **401**, i.e., from the left edge to the right edge of the display panel **401**, wherein the wide-screen movie **3301** is displayed horizontally between the upper cutout **601** and the lower cutout **601**.

Furthermore, the displayed screen content may comprise an upper horizontal matte region **3302** (e.g., a black bar) located above the wide-screen movie **3301**. The upper horizontal matte region **3302** extends into the area of the upper cutout **601**, such that the upper cutout **601** is accommodated, at least in part, in the upper horizontal matte region **3302**. A lower horizontal matte region **3303** (e.g., a black bar) may be located below the wide-screen movie **3301** and may extend into the area of the lower cutout **601**, such that the lower cutout **601** is accommodated, at least in part, in the lower horizontal matte region **3303**.

As shown in the non-limiting example, as per FIG. **33**, the upper horizontal matte region **3302** may have a height that is equal to the height of the upper cutout **601**, and, likewise, the lower horizontal matte region **3303** may have a height that is equal to the height of the lower cutout **601**. In other embodiments, such as the example shown in FIG. **34** (or FIG. **35**), the height of the upper and/or lower horizontal matte region **3302**, **3303** may be greater (or smaller) than the height of the cutout(s) **601**.

A first thin border **301** (of the casing) may be disposed adjacent to the left side of the wide-screen movie **3301**, and a second thin border **301** may be disposed adjacent to the right side of the wide-screen movie **3301**, such that the outer horizontal measurement of the smartphone’s casing is nearly equal to the image width of the wide-screen movie **3301**, that is, the size of the wide-screen movie **3301** is maximized in relation to the outer dimensions of the smartphone **100**, despite the front-facing camera **102**.

FIG. **34** shows an example in which the display screen **101** of the smartphone **100** has cutouts **601** at all four corners. The user may hold the smartphone **100** horizontally (landscape mode), and the wide-screen movie **3301** is displayed using the full width of the display screen **101**. As can be seen in the drawing, the wide-screen movie **3301** is completely visible—no corners of the movie **3301** are cut off by the cutouts **601**. The embodiment, as per FIG. **34**, is able to display the movie larger than a conventional smartphone (with the same dimensions of the casing).

With reference to FIG. **33** and FIG. **34**, in some embodiments, the casing or outer housing frame of the smartphone **100** may have strongly rounded corners **3304** with a curvature radius that is greater, or significant greater, than the width of the thin borders **106**, **107**, **301** at the left, right, top, and/or bottom edge of the display panel **401**. For example, as shown in FIG. **33** and FIG. **34**, the curvature radius of the rounded corners **3304** of the casing may be approximately

25

equal to the curvature radius of the cutout(s) **601**, which, as described above, have the shape of a quarter circle, and, as a result, the front-facing lens **102** of the camera or the optical emitter **1001** essentially is wrapped symmetrically between a rounded corner **3304** of the casing and a rounded cutout **601**. This approach may minimize the size or volume of the smartphone's casing while the area of the display panel **401** is maximized. For example, this is advantageous when putting the smartphone **100** in a pocket.

In other embodiments, the cutouts **601** may have a shape that is different from the quarter circles shown in FIG. **33** and FIG. **34**. For example, FIG. **35** shows an embodiment in which the upper and lower cutout **601** has the shape of a rectangle with rounded corners. In yet another embodiment, the cutouts **601** may have the shape of a square. Furthermore, the display panel **401** can have any suitable aspect ratio, as indicated by means of curved break lines in FIG. **33** and FIG. **35**.

When taking a self-portrait photograph ("selfie") or when recording a video with the front-facing camera (lens **102**), the operating state of the front-facing camera (i.e., the front camera module **402**) may be indicated on the display screen **101** by means of a quarter circle **3601** that surrounds the lens **102** of the front-facing camera—as shown in FIG. **36**. The graphic content displayed within the quarter circle **3601** may represent a schematized camera lens symbol or status indicator. Furthermore, the graphic content displayed within the quarter circle **3601** may be animated and may indicate operating modes or states of the front-facing camera, such as "recording," "ready," "standby," "inactive," "flashlight required," etc. Optionally, in some embodiments, the animation of the graphics within the quarter circle **3601** involves a rotation, wherein the lens **102** of the front-facing camera may constitute a fictitious pivot point.

In the present example as per FIG. **36**, the schematized camera lens symbol or status indicator (quarter circle **3601**) is located adjacent to the upper-right cutout **601** of the display panel **401**. However, in other embodiments, for example, if the lens **102** is located at another corner, or if the smartphone **100** features a second front-facing camera (see lens **701** in FIG. **7**), the schematized camera lens symbol or status indicator (quarter circle **3601**) may surround another cutout **601** of the display panel **401**.

The screen content, shown in the example as per FIG. **36**, comprises a viewfinder image (self-portrait photograph or video) that seamlessly extends from the upper edge of the display screen **101** to the lower edge of the display screen **101**. The screen content is displayed without a status bar **3201** to maximize the size of the viewfinder image and to make it possible to display the quarter circle **3601** that surrounds the cutout **601**. Surrounding a cutout **601** with a quarter circle **3601** means, in this context, that the endpoints of the quarter circle **3601** abut the vertical and horizontal edges of the display screen **101**, as shown in FIG. **36**.

The above approach improves the visual representation because by using a camera lens symbol or status indicator in the shape of a quarter circle **3601** that surrounds the cutout **601** and, thus, the lens **102**, it is possible to display a prominent and relative large status indicator (indicating operating modes or states of the front-facing camera), while, at the same time, the remaining or available space for the viewfinder image is maximized. It is well known that if, for example, a camera status icon is too small or "lost" in a status bar full of icons, the user may miss to stop a running recording, etc.

Optionally, when displaying a photograph or an other image in full screen on the display screen **101** (using the full

26

width and height of the display panel **401**), the corner regions of the photograph, as displayed on the display panel **401**, may be faded to black seamlessly, especially at corners with a cutout **601**. In this way, the cutout(s) **601** may be less noticeable. The corner(s) of the photograph may also be faded to another color, for example, the color of the casing of the smartphone **100**.

In FIG. **4**, the lens **102** of the front-facing camera at the location of the cutout **601** is disposed beneath the cover glass **405**. However, in other embodiments, the cover glass **405** may have a small hole or opening at the location of the lens **102**, and the lens **102** may be placed inside the hole, such that the lens **102** slightly protrudes from the cover glass **405**. This may maximize the length of the lens system of the camera module **402**, as the length of a lens system can be a limiting factor for taking high quality pictures. Furthermore, the solutions described in this disclosure make it possible to produce particularly thin smartphones **100**.

It is to be expressly noted that the cutout(s) **601** at the corner(s) of the display panel **401**, **1702** may accommodate optical and/or acoustic sensors and/or emitters of any applicable known or convenient type, including, but not limited to, proximity sensors, light sensors, infrared sensors, ultraviolet sensors, LED indicators, flashlights, optical infrared emitters (e.g., infrared LEDs), fingerprint sensors, iris scanners, sensors for face recognition, face tracking, or eye tracking, ultrasonic proximity sensors, or loudspeakers (e.g., piezoelectric speakers or other acoustic emitters). It should also be noted that the positions of the optical and/or acoustic sensors and/or emitters in the drawings can be swapped or duplicated as needed.

For example, FIG. **37** shows an embodiment with cutouts **601** at all four corners of the display screen **101**, and an acoustic emitter **3701**, e.g., a loudspeaker, is disposed at the location (or close to the location) of each cutout **601**. The four acoustic emitters or loudspeakers **3701** are connected to the I/O interface **204** of the computer system **200**, and when emitting sound, the user receives sound from all four corners of the smartphone **100**. A computer game **3702** may be executed on the computer system **200**. The computer game **3702** may be displayed in full screen on the display screen **101**, with the uppermost part of the computer game **3702** being displayed between the upper cutouts **601** and the lowermost part between the lower cutouts **601**. As a result, the size of the computer game **3702** is maximized in relation to the outer dimensions of the smartphone **100**.

FIG. **38** through FIG. **41** show another example: The smartphone **100** features a display screen **1601** with curved edges at the left, right, and at the top—corresponding to the seventh embodiment (FIG. **16** and FIG. **17**). Both upper cutouts **601** have a plurality of small holes or openings **1801** for an ear speaker **1802** on the left and an ear speaker **1803** on the right (not shown). Furthermore, the cutout **601** at the upper-right corner accommodates a first front-facing camera (lens **102**) and an electronic flashlamp (flash LED **801**); the cutout **601** at the upper-left corner accommodates a second front-facing camera (lens **701**) and an optical indicator (LED indicator **105**). The optical indicator **105** may indicate, by way of example, that the accumulator of the smartphone **100** is charging.

Optionally, as depicted in FIG. **42**, a conventional keyboard **4201** with mechanical keys may be integrated at the bottom of the smartphone **100**. While a mechanical keyboard **4201** may be beneficial for typing, the upper edge of the display screen **101** may still feature a thin border **301** or a curved edge **1603** (see FIG. **16**), thereby maximizing the size of the display screen **101**. Moreover, due to the thin

border **301** at the upper edge of the display screen **101**, it may be possible to combine a mechanical keyboard **4201** with a wide-screen display panel **401**, **1702** that has an advantageous aspect ratio, such as 16:9.

The thin borders **106**, **107**, **301** at the left, right, top, and/or bottom edge of the display panel **401** may have any suitable width, for example the width of the borders **106**, **107**, **301** shown in FIG. **35**, FIG. **42**, or FIG. **43**. In other embodiments the borders **106**, **107**, **301** may be extremely thin, such that essentially, the borders become nearly invisible and may be referred to as “borderless,” “bezel-less,” or “bezel-free” in general language usage. Furthermore, a display screen **101** with thin borders may be referred to as an “edge-to-edge display,” and the cover glass **405**, **1701** may have edges known as a 2D, 2.5D, or 3D curved glass display.

In the figures of the present disclosure, aspects of the invention are illustrated using a smartphone **100** and a smartwatch **1900**. Yet, any other electronic device can be used, including, but not limited to, mobile phones, phablets, tablet computers, subnotebooks, laptops, game consoles, or wearable computers (also known as body-borne computers or wearables, e.g., a touchscreen device or display integrated into clothing). Furthermore, the electronic device may feature, by way of example, a folding display (e.g., foldable OLED screen) or collapsible display. The display panel **401**, **1702** may be a flexible display, rollable display, elastic display, 3D display, autostereoscopic 3D display, holographic display, or any other applicable known or convenient type.

FIG. **43** shows an example of a foldable smartphone **100** with a foldable display screen **101**. The folding edge or bending edge **4301** is indicated by means of a dot-dash line. In other embodiments, the folding edge **4301** may be vertical (instead of horizontal, as depicted in FIG. **43**). The smartphone **100** features two front-facing cameras (lenses **102** and **701**) and two optical emitters (Flash LED **801** and IR-LED **1001**) located in the upper cutouts **601** that have a vertical, oblong shape. A fingerprint sensor **903** is located in each lower cutout **601**.

The borders **106**, **107**, **301** (or “thin borders,” as used in the claims) that surround the display screen **101** shall be defined as the distance between the outer housing frame of the mobile electronic device **100** and the beginning of the active screen area (which displays the screen content). Furthermore, the term “screen content,” as used in the claims, shall be interpreted as the entire, all-encompassing content displayed on the display screen **101**.

The conjunction “or,” as used in the claims, shall be interpreted as an alternative between two (or more) features and shall not be construed to specifically exclude any “non-selected” feature (such as an “XOR” operator). A list of features connected with an “or” that starts with the phrase “at least” or that ends with the phrase “a combination thereof” covers both single features from the list as well as any groups of features thereof.

Although the description above contains many specificities, these should not be construed as limiting the scope of the embodiments but as merely providing illustrations of some of several embodiments. Thus, the scope of the embodiments should be determined by the appended claims and their legal equivalents, rather than by the examples given.

What is claimed is:

1. A method of making a mobile electronic device with a front-facing camera so that the screen surface is maximized while the outer dimensions are minimized, said method comprising:

- a) providing a display panel with at least a first cutout at the upper-left corner and a second cutout at the upper-right corner, said display panel having an upper display panel edge, a left display panel edge, and a right display panel edge,
- b) providing at least one front-facing camera,
- c) disposing said at least one front-facing camera, at least in part, in the area of said first cutout or in the area of said second cutout,
- d) bending said upper display panel edge, located between said first cutout and said second cutout, to the rear of said display panel, so that the outer vertical measurement of said display panel is reduced while keeping the utilizable surface area of said display panel,
- e) bending said left display panel edge, located below said first cutout, and said right display panel edge, located below said second cutout, to the rear of said display panel, so that the outer horizontal measurement of said display panel is reduced while keeping the utilizable surface area of said display panel,

whereby said first cutout and said second cutout prevent the upper-left corner and the upper-right corner of said display panel from getting crumpled due to the bent upper display panel edge.

2. The method of claim **1**, further comprising:

- a) providing a computer system, said computer system being connected to said display panel and said front-facing camera,
- b) configuring said computer system to display a photograph on said display panel, wherein said photograph extends over the entire surface area of said display panel from said left display panel edge to said right display panel edge, and from said upper display panel edge to the lower edge of said display panel, the uppermost part of said photograph being displayed between said first cutout and said second cutout.

3. A mobile electronic device having a front-facing optical sensor, a maximized screen surface, and minimized outer dimensions, said mobile electronic device comprising:

- a) a display panel with at least a first cutout at the upper-left corner and a second cutout at the upper-right corner, said display panel having an upper display panel edge, a left display panel edge, and a right display panel edge, wherein:

- i) said upper display panel edge, located between said first cutout and said second cutout, is bent to the rear of said display panel, so that the outer vertical measurement of said display panel is reduced while keeping the utilizable surface area of said display panel,

- ii) said left display panel edge, located below said first cutout, and said right display panel edge, located below said second cutout, are bent to the rear of said display panel, so that the outer horizontal measurement of said display panel is reduced while keeping the utilizable surface area of said display panel,

whereby said first cutout and said second cutout prevent the upper-left corner and the upper-right corner of said display panel from getting crumpled due to the bent upper display panel edge,

- b) at least one front-facing optical sensor disposed, at least in part, in the area of said first cutout or in the area of said second cutout,

29

c) a computer system connected to said display panel and said front-facing optical sensor.

4. The mobile electronic device of claim 3, wherein said front-facing optical sensor at the location of said first or second cutout fills the void at the level of said display panel at least in part.

5. The mobile electronic device of claim 3, further comprising a mechanical keyboard located below said display panel, said mechanical keyboard being connected to said computer system.

6. The mobile electronic device of claim 3, wherein:

a) said front-facing optical sensor is a first front-facing camera and is disposed, at least in part, in the area of said first cutout,

b) a second front-facing camera is disposed, at least in part, in the area of said second cutout, said second front-facing camera being connected to said computer system,

c) said computer system is configured or programmed to process at least a part of the image data captured by said first front-facing camera and said second front-facing camera, wherein the interaxial separation between said first front-facing camera and said second front-facing camera is used to generate data based on stereoscopic information.

7. The mobile electronic device of claim 3, wherein:

a) at least one optical infrared emitter is disposed, at least in part, in the area of said first cutout or in the area of said second cutout, said optical infrared emitter being capable of illuminating the face of a user at least partially,

b) said computer system is configured or programmed to perform a face recognition using at least a part of the data of said front-facing optical sensor.

8. The mobile electronic device of claim 3, wherein said display panel has a third cutout at the lower-left corner and a fourth cutout at the lower-right corner, and wherein the lower edge of said display panel, located between said third cutout and said fourth cutout, is bent to the rear of said display panel, so that the outer vertical measurement of said display panel is reduced while keeping the utilizable surface area of said display panel.

9. The mobile electronic device of claim 8, wherein a first acoustic emitter is disposed at the location of said first cutout, a second acoustic emitter is disposed at the location of said second cutout, a third acoustic emitter is disposed at the location of said third cutout, and a fourth acoustic emitter is disposed at the location of said fourth cutout, each of said acoustic emitters being connected to said computer system, whereby the user receives sound from all four corners of said mobile electronic device.

10. The mobile electronic device of claim 3, further comprising a touch key located in the area of said first or second cutout in front of said front-facing optical sensor, said touch key being connected to said computer system, wherein said computer system is configured or programmed to execute a function as soon as said touch key is tapped.

11. The mobile electronic device of claim 10, further comprising a printed symbol that is printed on a transparent layer in front of said front-facing optical sensor in the area of said first or second cutout, wherein said printed symbol surrounds said front-facing optical sensor at least in part.

12. The mobile electronic device of claim 3, wherein the height of said first cutout substantially is equal to the width of said first cutout, said first cutout having, at least in part, the shape of a quarter circle, and wherein the height of said

30

second cutout substantially is equal to the width of said second cutout, said second cutout having, at least in part, the shape of a quarter circle, whereby the remaining screen surface of said display panel is maximized.

13. The mobile electronic device of claim 12, wherein said front-facing optical sensor is a front camera module with a front-facing lens, said front-facing lens being disposed, at least in part, in the area of said first cutout or in the area of said second cutout, wherein said front-facing lens is partially surrounded by the border of said first or second cutout substantially at a constant or minimized distance, whereby the remaining screen surface of said display panel is maximized.

14. The mobile electronic device of claim 13, further comprising a casing, wherein, in front view, said casing has rounded corners with a curvature radius that is substantially equal to the curvature radius of said first cutout or said second cutout, such that said front-facing lens essentially is wrapped symmetrically between two rounded corners of said casing and said first or second cutout, whereby the size or the volume of said casing is minimized while the screen surface of said display panel is maximized.

15. The mobile electronic device of claim 3, wherein said computer system is further configured or programmed to:

a) determine the relevance of at least one affected screen object that overlaps with the area of said first cutout or said second cutout,

b) determine the relevance of at least one blocking screen object that blocks the relocatability of said at least one affected screen object,

c) determine the least relevant screen objects from a list of screen objects, said list comprising at least said at least one affected screen object and said at least one blocking screen object,

d) reduce the size of at least one less relevant screen object, and shift at least one affected screen object that overlaps with the area of said first cutout or said second cutout.

16. The mobile electronic device of claim 15, wherein said computer system is further configured or programmed to display a setup option on said display panel, wherein said setup option allows the user to configure the relevance of object categories as a user preference.

17. The mobile electronic device of claim 3, wherein said computer system is further configured or programmed to determine by means of optical character recognition whether an image that overlaps with the area of said first cutout or said second cutout contains relevant symbols or characters in the image area that overlaps with said first or second cutout.

18. The mobile electronic device of claim 17, wherein said computer system is further configured or programmed to move relevant symbols or characters contained in the image area that overlaps with said first or second cutout to another location within said image by means of image processing at the bitmap level.

19. The mobile electronic device of claim 3, wherein:

a) said mobile electronic device is a smartphone,

b) said display panel is a flexible display having a flexible substrate,

c) said front-facing optical sensor is a front-facing camera, a light sensor, an infrared sensor, an ultraviolet sensor, a proximity sensor, a fingerprint sensor, an iris scanner, or a sensor for face recognition, face tracking, or eye tracking.

* * * * *